



উত্তরবঙ্গ কৃষি বিশ্ববিদ্যালয়

পুণ্ডিবাড়ী,কোচবিহার,পশ্চিমবঙ্গ-৭৩৬১৬৫

UTTAR BANGA KRISHI VISWAVIDYALAYA

P.O. PUNDIBARI, DIST. COOCH BEHAR, WEST BENGAL- 736165

ড: শুভেন্দুবন্দ্যোপাধ্যায়
নিয়ামক (ভারপ্রাপ্ত)
Dr. Subhendu Bandyopadhyay
Registrar (Acting)

ফোন/Phone: 03582-270143 (O)

ফ্যাক্স/Fax : 03582-270143

ইমেল/E-mail: registrarubkv@gmail.com

ওয়েবসাইট/Website: www.ubkv.ac.in

Tender No: UBKV/Est. (T& P-02) /43/2018-19 Dated: 13/02/2019

NOTICE INVITING TENDER (NIT)

Sealed tenders are invited under Two Bid System viz, Part-I Technical Bid and Part II Financial Bid from the intending reputed, bonafied and experienced Manufacturers / Exclusive Dealers / Authorized Dealer for supplying Equipment/ Instruments, furniture and computer with peripherals as per following specification.

a. List of Equipment/ Instrument with specification:

Sl No.	Name of Department	Name of Item	Specifications	Preferred Make/Model
1	Agronomy	Hot Plate (2 feet x 3 Feet)	<ul style="list-style-type: none">Top Plate Dimension : 2' x 3'Top Plate Material : SS TopTemp Range : 150-500°CMax Load : upto 10 KgPower Requirement : 240VAC-50HzWarranty : 2 Years(Mandatory)[Otherwise tender will be cancelled]	Any Good Make with ISO 9001: 2008 certification
2		Hot Plate SS Body with SS Top (18"x 24")	<ul style="list-style-type: none">Top Plate Dimension : 18" x 24" x 6"Top Plate Material : Stainless SteelTemp Range : 150-500°CMax Load : upto 10 KgPower Requirement : 240VAC-50HzWarranty : 2 Years(Mandatory)[Otherwise tender will be cancelled]	Any Good Make with ISO 9001: 2008 certification
3		Rotary Shaker	<p><u>Continuous Duty Rotary Shaker:</u></p> <ul style="list-style-type: none">Type : Variable orbital rotary motionThe shaker built on a iron-angle chassis resting on vibration absorbing rubber feet.Cabinet shall be made of M.S. sheet (18 SWG) coated with epoxy paint finish.Dynamically balanced mechanism comprising of triple eccentric-shaft drive with H.T springs on four corner for counter balancing of uniform vibration free rotation with load.Orbital shaking mechanism is built through a triple eccentric drive continuous dutyPowerful ball bearing 'DC'-drive 2HP PMDC-Motor, belt driven rotating platform with rotor on nine ball bearing in a circular orbit for very smooth movement.Stepless and adjustable auto-speed regulator from: 50-200 r.p.m with proximity circuit for counting r.p.m shall be provided.Heavy gauge Stainless sheet (304) Shaking tray fitted with S.S. (304) lotus type clamps For holding conical flasks of 200-1000 ml.Size of each tray: 60 X 60 cm (made of S.S. 304)Power requirement: Single phase 220/230 Volts, AC mains.Warranty : Minimum of 2 Years (Mandatory)[Otherwise tender will be cancelled]	Any Good Make with ISO 9001: 2008 certification

4		Digestion Chamber (Hooded, Stainless steel make)	3'x5'x3' with Exhaust fan, Sound proof, Acid Fume neutraliser facility with Glass Anti-chamber	Any Good Make with ISO 9001: 2008 certification
5		Digestion Chamber (Hooded, Stainless steel make)	3'x2.5'x2' with Exhaust fan, Sound proof, Acid Fume neutraliser facility with Glass Anti-chamber	Any Good Make with ISO 9001: 2008 certification
6		Flame Photometer	<p>Microcontroller Based Flame Photometer with Compressor Flame Photometer with Na, K & Ca filters, set of 5 glass beaker, capillary tube, drain pipe, RS-232cable, Compressor.</p> <ul style="list-style-type: none"> • Range : Na: 0.1 - 100 ppm ; Up to 250 meq/L, 1:100 dil <ul style="list-style-type: none"> ▪ K: 0.1 - 100 ppm ; Up to 250 meq/L, 1:100 dil ▪ Ca: 15-100ppm; Up to 250 meq/L, 1:100 dil • Sensitivity : Na: 0.5 ppm, K: 0.5 ppm, Ca: 15 ppm • Resolution : 0.1 ppm/meq • Reproducibility : ±2% FS & ± 2 digit • Minimum Sample : 3 ml/Element • Curve fit accuracy : ± 2% FS • Averaging : 2 to 15 Sec • Display : 128 x 64 graphical LCD display • Storage : upto 700 results • Flame System : LPG and dry oil free air • Detector : Silicon photodiode • Calibration : Up to 5-point calibration with curve fitting software • Gas Control : Fully adjustable • Ignition System : Auto Ignition • Atomizer : Axial flow type • Interface : RS-232 & PC Software • Power : 230 V, 50Hz <p>➤ Compressor Unit :</p> <ul style="list-style-type: none"> • Features : Fitted with Air Filter & Regulator • Air Supply : Oil free compressor unit with pressure regulator • Combustion Gas LPG: Controlled by precision regulator • Power : 230 V, 50Hz • Warranty : Minimum of 2 Years (Mandatory)[Otherwise tender will be cancelled] 	Preferred Make/Mode 1 : Systronics 128+126 /Equivalent
7		Hot Air Oven	<ul style="list-style-type: none"> • Size : 3' X 5' X 3' • Temperature Range : 50° C to 250° C • Accuracy : ± 1°C. • Temperature control : Digital Temp. Indicator Cum controller with PT-100 Sensor . • Power Requirement : 230 volts, 50 Hz, Single phase • Construction : <ul style="list-style-type: none"> ❖ The unit is double walled construction, ❖ Inner chamber is made (304 Quality) 24 gauge Stainless Steel Sheet with highly polished. ❖ Outer Chamber is made of mild steel sheet with epoxy paint ❖ Thick glass wool insulation ❖ 3 nos Stainless steel perforated Trays ❖ Fitted with control panel main 	Any Good Make with ISO 9001: 2008 certification

			<p>indicating neon lamp, load neon lamp, 3 Heat Rotary switch for low/medium/ high Temp.</p> <ul style="list-style-type: none"> • Warranty :2 years (Mandatory) [Otherwise tender will be cancelled] 	
8		Infrared Thermometer with Inbuilt Display	<ul style="list-style-type: none"> • Calibration Uncertainty : ± 0.3 C, when target and detector temperature are within 20 C (-20 to 65 C) • Calibration Uncertainty : ± 0.5 C, when target and detector temperature are different by more than 20 C (-40 to 80 C) • Measurement Repeatability : ± 0.1 C • Stability (Long-term Drift): less than 2 % change in slope per year when germanium filter is maintained in a clean condition • Response Time : 0.2s • Field of View : 22° half angle • Spectral Range : 8 to 14 μm; atmospheric window • Operating Environment: 0 to 50 C, < 90 % non-condensing relative humidity • Warranty : 2 Years(Mandatory) 	Apogee MI200 Series/ Equivalent
9		Round Brass Mesh Sieve	2mm	Any Good Make
10		Brass Soil Thermometer	15 cm	Any Good Make
11		Brass Soil Thermometer	20cm	Any Good Make
12		Handheld Green Seeker with Inbuilt Display	<ul style="list-style-type: none"> • Display Screen : LCD • Range:0.00-0.99 • Battery :3.7VDC nominal, 1130 mAh • Charging Time : 5 hour (full charge) • Material :Xenoy plastic • Rating : IP54 • Emission Wavelength : Red: 660 nm, ~25 nm FWHM <ul style="list-style-type: none"> ▪ NIR: 780 nm, ~25 nm FWHM • Field of View : 10" at 24", 20" at 48" • Height Range :24" - 48" • Remote trigger switch port :2.5 mm stereo phone jack • Supplied complete with : Sensor battery ,Wrist strap,AC charger , USB-to-microUSB cable, Carrying pouch ,Quick Reference Card, Fertilizer Estimation Chart • Warranty : 2 Years (Mandatory) 	Trimble Handheld Crop Sensor /Equivalent
13		Square Cuvettes	Suitable for Visible Spectrophotometer Cecil 1011	
14		Hulling Machine (Rubber)	RICE SHELLER <ul style="list-style-type: none"> • Capacity : 40-50kg/hr • Shelling Mechanism : Comprises of two rubber roller • Rubber roller : 100mm x 35mm (approx) • Husk Collector : To collect husk from each sample for further analysis • Operating Voltage : 220V, 50Hz, A.C. • Motor : 0.25 HP Single Phases (180W) • Size : 700 (L) x 330 (W) x 817 (H) mm (approx.) • Weight : 41 Kg (approx.) • Warranty : 2 Years 	Indosaw/Agrosaw/ Equivalent
15		Mortar and Pestle		Any Good Make
16		Rice Testing Mill (Rice Polisher) With timer	<ul style="list-style-type: none"> • Capacity : 100 g/batch • Operating Voltage : 220V, 50Hz AC • Bran Collector : to collect bran for each sample for further analysis • Size : 590 x 340 x 370 mm (approx.) • Weight : 48 Kg 	Indosaw /Agrosaw / Equivalent

			<ul style="list-style-type: none"> • Motor : ½ HP • Mesh Size of abrasive roller : 30 no. • Roll speed range : 650 – 1750rpm • Warranty : 2 Years 	
17		Groundnut Decorticator		Any Good Make
18		Weighing Balance 1000 - 5000 g (plastic made)	<ul style="list-style-type: none"> • Analog Dial • Capacity up to 5 kg and readability standard • Pan size: standard 	Any Good Make
19		Bench Top pH Meter	<p>Type : Bench Top</p> <p>pH Range :</p> <ul style="list-style-type: none"> • Range -1.99 to 16.00 • Resolution 0.01 pH • Accuracy ±0.002 • Cal. Points Up to 5 points <p>ORP Range :</p> <ul style="list-style-type: none"> • Range ±1999 mV • Rel. mV Range ±1999 mV • Resolution 0.1 mV (±199.9 mV) / 1 mV (beyond) • Accuracy ±0.2 mV (±199.9 mV) / ±2 mV (beyond) <p>Temperature Range :</p> <ul style="list-style-type: none"> • Range 0.0 to 100.0 °C / 32.0 to 212.0 °F • Resolution 0.1 °C / 0.1 °F • Accuracy ±0.5 °C / ±0.9 °F • Compensation Automatic or Manual (0 to 100 °C / 32 to 212.0 °F) <p>Memory : Minimum 100 Data sets</p> <p>Power Requirements : 9-12 V DC adapter, 3.0-3.5 A (100/240 VAC, SMPS)</p> <p>Supplied complete with : pH Meter with pH Electrode, ATC Probe , Integral Electrode, User Manual, Power adapter and set of 3 buffers</p> <p>Warranty : 2 Years</p>	Eutech Cyber scan pH 700(ECPH 70042S) /Metler Toledo FP-20
20		Bench Top Conductivity Meter	<p>EC range : 0.00 µS/cm to 200 mS/cm</p> <p>TDS range : 0.00 to 50 mg/L</p> <p>Temperature : 0 to 100°C</p> <p>Resolution :</p> <ul style="list-style-type: none"> • EC- 0.01 / 0.1 / 1 µS ; 0.01 / 0.1 mS , • TDS- 0.01 / 0.1 / 1 ppm ; 0.01 / 0.1 ppt <p>Accuracy @ 25°C :</p> <ul style="list-style-type: none"> • ±1% of EC reading ± (0.05 µS/cm) • ±1% of TDS reading ± (0.03 mg/L) <p>Warranty : 2 Years</p>	Eutech Cyber scan Cond 700 (ECCON7004 3S) / Metler Toledo FP30
21		Kjeldahl Digestion tube(250ml)	Suitable for Pelican Kelplus Digestors	Kelplus/Equivalent
22		Root Analyzer	<p>Root Scanner System should be based on research grade and worldwide accepted to analyze washed roots.</p> <p>System should have following specifications:</p>	Regent WinRhizo STD4800 Basic

			<ul style="list-style-type: none"> ➤ Roots measured automatically after extraction from soil and washed ➤ Before Analysis, the roots are digitised with a scanner ➤ Scanner should have special lighting system to avoid shadows ➤ System should be permanently calibrated to increase the measurement precision ➤ System should be able to analyse overlapped root and filtering out the debris based on area, shape. ➤ Analysis roots using desktop scanner, suitable for image acquisition of macroscopic objects like roots ➤ Scanner : 22 x 30 cm for Standard Area ➤ Accessories : For Root positioning & scanning. ➤ Measured Parameters Root Morphology i.e. Total Length, Average diameter, Total area, volume, number of tips, forks & crossings ➤ Bidder should enclose >5 copy of successful installations with user contact details ➤ Bidder should enclose >5 copy of International Publication of quoted model ➤ Warranty : 2 Years 	
23		Trays for growing paddy seedling	Plastic Make : Size 1.5' x 1.5'	
24		Tube Auger	Iron Make	Any Good Make
25		Tensiometer 24"	Standard Tensiometer with ceramic porous cup	Any Good Make
26	Animal Science	Automatic Soxhlet Equipment	Automatic Soxhlet Equipment (for analysis of feed, fodder, biomaterials etc., complete set of 2 (two) place programmable PC, compatible solvent extraction unit with data logger and display including essential accessories with installation, demonstration and commissioning etc and additional 4 (four) glass condensers and eight (8) oil flasks	Pelican SOCS PLUS /Equivalent
27		Automatic FiberAnalyzer Equipment	Automatic FiberAnalyzer Equipment (for analysis of feed, fodder, biomaterials etc., complete set of automatic PC compatible 2 (two) place Fiber Estimation System with data logger and display including essential accessories with installation, demonstration and commissioning etc and additional 4 (four) glass condensers and eight (8) additional glass wares.	Pelican FIBRA PLUS /Equivalent
28		Automatic Digestion Equipment along with Acid Neutralization Unit	<p>Automatic Digestion Equipment(for analysis of feed, fodder, biomaterials etc. samples), 4 (four) places for 250 ml capacity, digestion system o with essential accessories including installation, demonstration and commissioning etc</p> <p>Digestor</p> <ul style="list-style-type: none"> • Twenty Place 250 ml capacity PC Compatible Block Digestion System with digital display. • Aluminium Block with Casted Aluminium Alloy Heaters , • RS 232 interface for PC/Laptop Connectivity, • Integrated autosequencing time/temperature domain of 2 programs and 8 sequencing steps, • Auto over temperature protection, Auto Sensor break protection, Auto Error Indication, • Inbuilt software program for micronutrient, macro nutrient, trace element, diacid and triacid. • All essential accessories like Digestion Tubes 250 ml - 20 Nos, SS Insert Rack, Exhaust Manifold, Suction assembly for safe removal of acid fumes, • Additional one set tubes & Insert Rack, ISO 9001: 2008 Certified. • Electrical Requirement: 230 V, 50 Hz AC Mains. • Additional 20 (twenty) numbers of 250 ml digestion tubes <p>Acid Neutralizer :</p> <ul style="list-style-type: none"> • Four Stage Fully Automatic Microprocessor based acid neutralization scrubber with digital display integrated online with motherboard of digestion system with inbuilt pump for water recirculation • Should automatically start on operation of digestion system, 	Pelican KEL PLUS /Equivalent

			<p>Should automatically stops on completion of digestion cycle with a delay time of 5 minutes to remove residual fumes.</p> <ul style="list-style-type: none"> • Auto waste disposal & auto drain of tank water after pre programmable consecutive operations, Incorporates indication of drain cycles, low level indication and high level indication, • Auto fill error in case of absence of inlet water in tank and the system automatically switches off with alarm. • Inbuilt auto error diagnostic and safety features. Electrical Requirement: 230v/50Hz AC Mains. • Warranty : 2 Years (Mandatory) 	
29		Automatic Distillation System	<p>Automatic Distillation System (for analysis of feed, fodder, biomaterials etc. samples), complete set with essential accessories including installation, demonstration and commissioning etc</p> <ul style="list-style-type: none"> • Autosequencing Microprocessor based PC Compatible Distillation with in-built software • Fully Automatic sequencing with auto Intelligent run of programmable steps, • Automatic Dilution, Automatic Alkali Addition, Automatic Steam Processing, Process over indication with alarm with delay time feature, Automatic titration connectivity feature for future upgradation, • Two line alpha numeric digital LCD display, • RS 232 interface for connectivity to PC, • Tube insert error indication, Auto door open warning indication, Auto deactivation of System on error diagnosis, Adjustable steam power, Automatic Reagent level sensor with alarm, • Auto online water saving mechanism, Stainless steel non corrosive steam Generator, • Fully Automatic water level monitoring with centrifugal refilling pump & Peristaltic pump for reagents addition, • ISO 9001: 2008 Certified. Electrical Requirement - 220 - 230V/50Hz. • Warranty : 2 Years (Mandatory) 	Pelican KEL PLUS /Equivalent
30		Urine Analyzer	<ul style="list-style-type: none"> • Bench-top portable Digital Urine Analyzer. • System: Semi-automated Urine strip analyzer • Type: Reflectance photometer • Measuring System: Wavelengths - 470, 540, 650 nm • Memory: 400 results • Throughput: 60 tests/hr in Normal Mode & 240 testes/hr in Smart mode • User interface: Color TFT LCD display • Printer: Built-in Thermal Printer • Certificates: CE • Physical Dimensions: 230 X 127 x 110 mm • Weight: 0.8 Kg • Test Strips: DekaPHAN Laura & MicroalbuPHAN Laura • Parameters: Specific Gravity, Leucocytes, Nitrite, pH, Protein, Glucose, Ketone, Urobilinogen, Bilirubin, Blood & Microalbumin, Creatinine • Optical QC: Grey QC strip • System Interface: Communication via RS232 & USB port • Host Protocol: Uni-directional • Sample Identification: Sample ID via keyboard entry, barcode reader • Power source: AC 90-230V/50-60 Hz • Power consumption: 20 W max./1 W standby • Onsite warranty for 2 year on damaged parts. • Additional reagent strip 100pc x 2cont. 	Transasia Laura SMART /Equivalent
31		Salinity meter	<p>Salt6+ Salinity Meter with Electrode ECCONSEN91B & Salinity Carrying Kit Set</p> <p>Warranty : 2 Years</p>	Eutech Product Code : ECSALT603 PLUSK , Cat No. 8003007

32	Fishery Unit	Portable Colorimeter for Aquaculture water Analysis	<table border="1"> <tr><td>Operate Mode</td><td>Absorbance, Concentration</td></tr> <tr><td>Precision</td><td>= 3%</td></tr> <tr><td>Lamp</td><td>Light emitting diode (LED)</td></tr> <tr><td>Calibration Mode</td><td>Support</td></tr> <tr><td>Power Supply</td><td>4AA alkaline batteries</td></tr> <tr><td>Operating Conditions</td><td>0 to 50 °C; 0 to 90% relative humidity (n</td></tr> <tr><td>Storage Conditions</td><td>- 25 to 50 °C (instrument)</td></tr> <tr><td>Dimensions (W*L*H*)</td><td>265mm x 121mm x 75mm</td></tr> <tr><td>Weight</td><td>630g</td></tr> <tr><td>Certificate</td><td>CE</td></tr> </table> <table border="1"> <thead> <tr><th>Parameter</th><th>Range</th><th>Resolution</th><th>Pri</th></tr> </thead> <tbody> <tr><td>pH value</td><td>6.5-8.5ppm</td><td>0.1ppm</td><td>= 3% ± 0</td></tr> <tr><td>Free chlorine</td><td>0.01-5.00ppm</td><td>0.01ppm</td><td>= 3% ± 0</td></tr> <tr><td>Dissolved oxygen</td><td>0.2-15.0ppm</td><td>0.1ppm</td><td>= 3% ± 0</td></tr> <tr><td>Ammonia nitrogen</td><td>0.02-6.00ppm</td><td>0.01ppm</td><td>= 3% ± 0</td></tr> <tr><td>Sulfide</td><td>0.02-1.00ppm</td><td>0.01ppm</td><td>= 3% ± 0</td></tr> <tr><td>Total alkalinity</td><td>10~200ppm</td><td>10mg/L</td><td>= 3% ± 1</td></tr> <tr><td>Calcium hardness (H)</td><td>5~400ppm</td><td>1mg/L</td><td>= 3% ± 1</td></tr> <tr><td>Magnesium hardness(H)</td><td>10~400ppm</td><td>1mg/L</td><td>= 3% ± 1</td></tr> <tr><td>Total hardness (H)</td><td>5~400ppm</td><td>1mg/L</td><td>= 3% ± 1</td></tr> <tr><td>Phosphate</td><td>0.03~4.00ppm</td><td>0.01mg/L</td><td>= 3% ± 0</td></tr> <tr><td>Nitrate nitrogen</td><td>0.5-15.0mg/L</td><td>0.1mg/L</td><td>= 3% ± 0</td></tr> <tr><td>Nitrite</td><td>0.003-0.500ppm</td><td>0.001ppm</td><td>= 3% ± 0</td></tr> </tbody> </table> <p>Warranty : 2 Years(Mandatory) Supplied complete with 100 nos Test Kits of each above parameter, carrying care, 4 nos AA Alkaline Batteries</p>	Operate Mode	Absorbance, Concentration	Precision	= 3%	Lamp	Light emitting diode (LED)	Calibration Mode	Support	Power Supply	4AA alkaline batteries	Operating Conditions	0 to 50 °C; 0 to 90% relative humidity (n	Storage Conditions	- 25 to 50 °C (instrument)	Dimensions (W*L*H*)	265mm x 121mm x 75mm	Weight	630g	Certificate	CE	Parameter	Range	Resolution	Pri	pH value	6.5-8.5ppm	0.1ppm	= 3% ± 0	Free chlorine	0.01-5.00ppm	0.01ppm	= 3% ± 0	Dissolved oxygen	0.2-15.0ppm	0.1ppm	= 3% ± 0	Ammonia nitrogen	0.02-6.00ppm	0.01ppm	= 3% ± 0	Sulfide	0.02-1.00ppm	0.01ppm	= 3% ± 0	Total alkalinity	10~200ppm	10mg/L	= 3% ± 1	Calcium hardness (H)	5~400ppm	1mg/L	= 3% ± 1	Magnesium hardness(H)	10~400ppm	1mg/L	= 3% ± 1	Total hardness (H)	5~400ppm	1mg/L	= 3% ± 1	Phosphate	0.03~4.00ppm	0.01mg/L	= 3% ± 0	Nitrate nitrogen	0.5-15.0mg/L	0.1mg/L	= 3% ± 0	Nitrite	0.003-0.500ppm	0.001ppm	= 3% ± 0	HACH /Octopus Inc/Merck /equivalent			
Operate Mode	Absorbance, Concentration																																																																														
Precision	= 3%																																																																														
Lamp	Light emitting diode (LED)																																																																														
Calibration Mode	Support																																																																														
Power Supply	4AA alkaline batteries																																																																														
Operating Conditions	0 to 50 °C; 0 to 90% relative humidity (n																																																																														
Storage Conditions	- 25 to 50 °C (instrument)																																																																														
Dimensions (W*L*H*)	265mm x 121mm x 75mm																																																																														
Weight	630g																																																																														
Certificate	CE																																																																														
Parameter	Range	Resolution	Pri																																																																												
pH value	6.5-8.5ppm	0.1ppm	= 3% ± 0																																																																												
Free chlorine	0.01-5.00ppm	0.01ppm	= 3% ± 0																																																																												
Dissolved oxygen	0.2-15.0ppm	0.1ppm	= 3% ± 0																																																																												
Ammonia nitrogen	0.02-6.00ppm	0.01ppm	= 3% ± 0																																																																												
Sulfide	0.02-1.00ppm	0.01ppm	= 3% ± 0																																																																												
Total alkalinity	10~200ppm	10mg/L	= 3% ± 1																																																																												
Calcium hardness (H)	5~400ppm	1mg/L	= 3% ± 1																																																																												
Magnesium hardness(H)	10~400ppm	1mg/L	= 3% ± 1																																																																												
Total hardness (H)	5~400ppm	1mg/L	= 3% ± 1																																																																												
Phosphate	0.03~4.00ppm	0.01mg/L	= 3% ± 0																																																																												
Nitrate nitrogen	0.5-15.0mg/L	0.1mg/L	= 3% ± 0																																																																												
Nitrite	0.003-0.500ppm	0.001ppm	= 3% ± 0																																																																												
34	Thermometer for tank	AUTIDEFY LCD Digital Aquarium Thermometer Fish Tank Water Terrarium Temperature	<ul style="list-style-type: none"> Submerge probe into fish tank to measure water temperature (Submerge probe only, do not submerge thermometer in water) Digital °C /° F thermometer; Temperature range -50°C ~ +70°C, Operating temperature -10°C ~ +50°C Easy to apply suction cup and easy to read LCD screen; Temperature readings to within 0.1 degree Powered by one LR44 button cell (included) Package Contents: 3 x Battery; 3 x Digital Thermometer; 3 x Probe 	AUTIDEFY /Equivalent																																																																											
35	Dissolved Oxygen meter	SPECIFICATIONS	<table border="1"> <tr><td>Circuit</td><td>Custom one-chip of microprocessor LSI circuit.</td><td>Operating Temperature</td><td>0 to 50 °C (32 to 122 °F)</td></tr> <tr><td>Display</td><td>Dual function meter's display, 13 mm(0.5"). Super large LCD display with contrast adjustment for best viewing angle.</td><td>Operating Humidity</td><td>Max. 80% RH.</td></tr> <tr><td rowspan="3">Measurement & Range</td><td>Dissolved Oxygen</td><td>0 to 20.0 mg/L(liter).</td><td>Sample Time</td><td>Approx. 0.4 sec.</td></tr> <tr><td>Oxygen in Air</td><td>0 to 100.0 %.</td><td>Power Supply</td><td>006P DC 9V battery(Hea</td></tr> <tr><td>Temperature</td><td>0 to 50 °C .</td><td>Power Current</td><td>Approx. DC 6.6 mA.</td></tr> <tr><td rowspan="3">Resolution</td><td>Dissolved Oxygen</td><td>0.1 mg/L.</td><td>Weight</td><td>335 g/0.74 LB (batterie</td></tr> <tr><td>Oxygen in Air</td><td>0.1 % O2 .</td><td rowspan="3">Size</td><td rowspan="3">Main instrument: 180 x 72 x 32 mm(7.1 x Oxygen probe : 190 mm x 28 mm Dia. (</td></tr> <tr><td>Temperature</td><td>0.1 .</td></tr> <tr><td>Accuracy (23 5)</td><td>Dissolved Oxygen</td><td>0.4 mg/L.</td><td>Accessories</td><td>Oxygen probe(OXPB-11 Carrying case..... Operation manual..... Spare Probe head with E OXHD-04..... Probe-filling Electrolyte OXEL-03.....</td></tr> <tr><td rowspan="3">Sensor Structure</td><td>Oxygen in Air</td><td>0.7% O2.</td><td rowspan="3">included</td><td rowspan="3">* Oxygen probe..... * Spare Probe head with * Probe-filling Electrolyt * RS232 cable..... * USB cable..... * Data Acquisition softw</td></tr> <tr><td>Temperature</td><td>0.8 °C /1.5 °F.</td></tr> <tr><td>Probe Compensation & Adj.</td><td>The polarographic type oxygen probe with an incorporated temperature sensor.</td></tr> <tr><td rowspan="3">Memory and Recall</td><td>Temperature</td><td>0 to 50 °C , Automatic</td><td rowspan="3">Optional Accessories</td><td rowspan="3">.....</td></tr> <tr><td>Salt</td><td>0 to 39 % Salt</td></tr> <tr><td>Height(M. T.)</td><td>0 to 3900 meter</td></tr> <tr><td>Power off</td><td>Records Maximum, Minimum and Average readings with RECALL.</td><td></td><td></td><td></td></tr> <tr><td>Over input indication</td><td>Auto power off saves battery life, or manual off by push button.</td><td></td><td></td><td></td></tr> <tr><td>Data Output</td><td>Indication of "- - -".</td><td></td><td></td><td></td></tr> <tr><td></td><td>RS 232 PC serial interface.</td><td></td><td></td><td></td></tr> </table>	Circuit	Custom one-chip of microprocessor LSI circuit.	Operating Temperature	0 to 50 °C (32 to 122 °F)	Display	Dual function meter's display, 13 mm(0.5"). Super large LCD display with contrast adjustment for best viewing angle.	Operating Humidity	Max. 80% RH.	Measurement & Range	Dissolved Oxygen	0 to 20.0 mg/L(liter).	Sample Time	Approx. 0.4 sec.	Oxygen in Air	0 to 100.0 %.	Power Supply	006P DC 9V battery(Hea	Temperature	0 to 50 °C .	Power Current	Approx. DC 6.6 mA.	Resolution	Dissolved Oxygen	0.1 mg/L.	Weight	335 g/0.74 LB (batterie	Oxygen in Air	0.1 % O2 .	Size	Main instrument: 180 x 72 x 32 mm(7.1 x Oxygen probe : 190 mm x 28 mm Dia. (Temperature	0.1 .	Accuracy (23 5)	Dissolved Oxygen	0.4 mg/L.	Accessories	Oxygen probe(OXPB-11 Carrying case..... Operation manual..... Spare Probe head with E OXHD-04..... Probe-filling Electrolyte OXEL-03.....	Sensor Structure	Oxygen in Air	0.7% O2.	included	* Oxygen probe..... * Spare Probe head with * Probe-filling Electrolyt * RS232 cable..... * USB cable..... * Data Acquisition softw	Temperature	0.8 °C /1.5 °F.	Probe Compensation & Adj.	The polarographic type oxygen probe with an incorporated temperature sensor.	Memory and Recall	Temperature	0 to 50 °C , Automatic	Optional Accessories	Salt	0 to 39 % Salt	Height(M. T.)	0 to 3900 meter	Power off	Records Maximum, Minimum and Average readings with RECALL.				Over input indication	Auto power off saves battery life, or manual off by push button.				Data Output	Indication of "- - -".					RS 232 PC serial interface.				Lutron DO5510 /Equivalent
Circuit	Custom one-chip of microprocessor LSI circuit.	Operating Temperature	0 to 50 °C (32 to 122 °F)																																																																												
Display	Dual function meter's display, 13 mm(0.5"). Super large LCD display with contrast adjustment for best viewing angle.	Operating Humidity	Max. 80% RH.																																																																												
Measurement & Range	Dissolved Oxygen	0 to 20.0 mg/L(liter).	Sample Time	Approx. 0.4 sec.																																																																											
	Oxygen in Air	0 to 100.0 %.	Power Supply	006P DC 9V battery(Hea																																																																											
	Temperature	0 to 50 °C .	Power Current	Approx. DC 6.6 mA.																																																																											
Resolution	Dissolved Oxygen	0.1 mg/L.	Weight	335 g/0.74 LB (batterie																																																																											
	Oxygen in Air	0.1 % O2 .	Size	Main instrument: 180 x 72 x 32 mm(7.1 x Oxygen probe : 190 mm x 28 mm Dia. (
	Temperature	0.1 .																																																																													
Accuracy (23 5)	Dissolved Oxygen	0.4 mg/L.			Accessories	Oxygen probe(OXPB-11 Carrying case..... Operation manual..... Spare Probe head with E OXHD-04..... Probe-filling Electrolyte OXEL-03.....																																																																									
Sensor Structure	Oxygen in Air	0.7% O2.	included	* Oxygen probe..... * Spare Probe head with * Probe-filling Electrolyt * RS232 cable..... * USB cable..... * Data Acquisition softw																																																																											
	Temperature	0.8 °C /1.5 °F.																																																																													
	Probe Compensation & Adj.	The polarographic type oxygen probe with an incorporated temperature sensor.																																																																													
Memory and Recall	Temperature	0 to 50 °C , Automatic	Optional Accessories																																																																											
	Salt	0 to 39 % Salt																																																																													
	Height(M. T.)	0 to 3900 meter																																																																													
Power off	Records Maximum, Minimum and Average readings with RECALL.																																																																														
Over input indication	Auto power off saves battery life, or manual off by push button.																																																																														
Data Output	Indication of "- - -".																																																																														
	RS 232 PC serial interface.																																																																														

36	Rotary Microtome	<ul style="list-style-type: none"> • Range of Section thickness 1 µm to 50 µm in steps of 1 µm • Front Located Feed Indicator & micron setting Knob Robust & advanced ratchet gear cam drive system for accurate feed • All locks & adjustments are readily accessible for fast & safe operation • Independent feed mechanism with safety locking device to lock the hand wheel • Microtome knife of special tool steel -120mm with handle in box. 	LABOVISION Magnacut/Equivalent
36	Single Beam Visible Spectrophotometer	<ul style="list-style-type: none"> • Spectrophotometers should be supplied with Bi-directional RS232 interface, mains cable, instruction manual, short form operating instructions and 10mm cell holder. • Lithrowmonochromator with 1200 lines/ mm holographic grating, coated optics. • Wavelength range : 325-1000nm , • Wavelength Accuracy :<1nm • Large Seven Segment bright LED for readouts. • Photometric Range : -0.3 -3A, 0 -200%T, 0 - 9999C • Photometric Accuracy : 0.005A or 1% whichever is greater • Photometric Noise : less than ±0.0002A at 500nm • Wavelength Precision: 0.1nm, Bandwidth : 8nm • Stray light :better than 0.05%, • Stability : ± 0.001A/hr • Automatic Peak Seek, Automatic Self test and Calibration • 4 position cell manual changer with 4 x 10mm Cell Holder • 10 mm Path length Quartz Cuvette • Warranty : 2 Years 	Perkin Elmer-Lambda 325 / Cecil-CE 1011/ Equivalent
38	Submersible pump	5 HP	CG/Equivalent
39	Aquaguard along with Iron Guard	For drinking and aquarium water	Aquaguard/Equivalent
40	Stand fan		Havells /CG/Equivalent
41	ELISA Reader	<ul style="list-style-type: none"> • Wavelength range : 400-750 nm • Photometric range : 0.0-3.5 OD • Linearity : ≤1.0% from 0.0-2.0 OD; ≤2.0% from 0.0-3.0 OD • Accuracy : ±1.0% or 0.010 from 0.000-3.000 OD at 490 nm • Precision : 1.0% or 0.005 OD from 0.0-2.0 OD; 1.5% from 2.0-3.0 OD • Resolution : 0.001 OD • Filter wheel capacity : 8 Wheel with 6 preinstalled filters with 415, 450, 490, 595, 655, and 750 nm • Plate shaking : 3 speeds: low, mid, high; duration: 0-999 sec • Read time : 6 sec at single wavelength,10 sec at dual wavelengths • Data output : Onboard graphical thermal printer and USB2 interface with PC or Mac data stations • Data storage : Calendar/clock function; 64 assay Protocols • Flexible configurations with ability to read flat-, U-, or V-bottom microplates or 8- or 12-well strip plates • Automatic calibration before each reading • Variable-speed plate-shaking capability • Easy-access 8-position filter wheel with 6 standard filters • USB2 port for external computer control • Data and protocol presentation on LCD display • Onboard data storage of protocols, standard curves, and graphs • Self-diagnostic capabilities to detect lamp burnout at startup 	Bio-Rad/ Thermo/ Equivalent

		<ul style="list-style-type: none"> Motorized door for plate loading <p>Software specification:</p> <ul style="list-style-type: none"> Microplate Manager for High-Throughput Analysis and Reporting Running of 12 separate assays on the same plate Optional automatic printing upon completion of measurement Multiple-plate processing with automated data export Custom reporting function that provides one-button screening for predefined assays, such as for TSE Comprehensive Curve-Fit Analyses • Linear, quadratic, cubic, Log-Log, Zero-Intercept Linear, Semi-Log, Logit Log, Point to Point or logistic (4-parameter, 5-parameter) fit types Linear or logarithmic automatic axis scaling External standard curves for multiple plates Curve-fit graph overlay for comparison Performance verification parameters include: Accuracy, Precision, Linearity Spectral blocking Complex Kinetic Analyses Choice of number of calculation points for Vmax Simple velocity calculation Negative or positive slope calculation Absorbance limit selection Kinetic correlation coefficient display and calculation for fit (r value) Real-time data acquisition display and ability to zoom in on a well Automatic scaling and real-time monitoring Warranty : 2 Years 	
42	Incubator Shaker	<ul style="list-style-type: none"> Volume/Size : 285Lit/ 20''x20''x24'' Shaking Tray : 18'' x 18 '' No. &Vol of Flask : 15 nos 250 ml Shelves : 2 nos Temp Range : Ambient to 90C Controller : PID Shaking Speed : 20-250 RPM Material : Inner Chamber with SS304 <ul style="list-style-type: none"> Outer body with MS -powder coated Door-Inner Glass Door & Outer Glass View Door Features : Auto Variac Control , RPM Counter, Digital Timer, Fluorescent Lights Power : 220/230V , Single Phase AC , 4KW Warranty : 2 Years (Mandetary, Otherwise bid will be cancelled) <p>** Supply complete with suitable voltage stabilizer</p>	Any Good Make with ISO 9001: 2008 certification
43	Ultrasonicator	<ul style="list-style-type: none"> Tank Volume (litres) : 12 L Ultrasonic Wattage : 200 W Ultrasonic Frequency : 40 ± 3 KHz Tank Dimension (Taper) : 300x240x200 LxWxH (mm) (Approx) Outer Dimension : 325x265x340 LxWxH (mm) (Approx) Heating : Ambient to 80°C Digitally Controlled (Dual Display) Digital Timer : 5 to 60 Minutes Tank Drain : Ball Valve Inner Tank Material : Stainless Steel Outer Housing Material : Stainless Steel Power Supply : 220 Volt, Ac 50 Hz, Single Phase Warranty : 2 years(Mandatory, Otherwise bid will be cancelled) 	Any Good Make with ISO 9001: 2008 certification
44	Benchtop	<ul style="list-style-type: none"> Double wall construction 	Any Good

		Chiller	<ul style="list-style-type: none"> • Inner chamber : Stainless Steel • Outer body : CRC sheet duly painted. • Fitted with Hermitically sealed compressor • Circulation system is applied by a circulation pump is capable to recirculation the bath liquid to other apparatus. • Control Panel is provided with the unit consisting of indicating lamp, plug and cable suitable 220/230 volt single phase A.C. main. • Inner Chamber : Stainless Steel • Temperature Control : Digital Temp. Indicator cum Controller. • Temp. Range : 0 to 10 deg.C • Tank capacity- : 10 lit. • Warranty: 2 years(Mandatory, Otherwise bid will be cancelled) 	Make with ISO 9001: 2008 certification
45	Soil Science and Agril. Chemistry	Flame Photometer	<p>Microcontroller Based Flame Photometer with Compressor Flame Photometer with Na, K & Ca filters, set of 5 glass beaker, capillary tube, drain pipe, RS-232cable, Compressor.</p> <ul style="list-style-type: none"> • Range : Na: 0.1 - 100 ppm ; Up to 250 meq/L, 1:100 dil <ul style="list-style-type: none"> ▪ K: 0.1 - 100 ppm ; Up to 250 meq/L, 1:100 dil ▪ Ca: 15-100ppm; Up to 250 meq/L, 1:100 dil • Sensitivity : Na: 0.5 ppm, K: 0.5 ppm, Ca: 15 ppm • Resolution : 0.1 ppm/meq • Reproducibility : ±2% FS & ± 2 digit • Minimum Sample : 3 ml/Element • Curve fit accuracy : ± 2% FS • Averaging : 2 to 15 Sec • Display : 128 x 64 graphical LCD display • Storage : upto 700 results • Flame System : LPG and dry oil free air • Detector : Silicon photodiode • Calibration : Up to 5-point calibration with curve fitting software • Gas Control : Fully adjustable • Ignition System : Auto Ignition • Atomizer : Axial flow type • Interface : RS-232 & PC Software • Power : 230 V, 50Hz <p>➤ Compressor Unit :</p> <ul style="list-style-type: none"> • Features : Fitted with Air Filter & Regulator • Air Supply : Oil free compressor unit with pressure regulator • Combustion Gas LPG: Controlled by precision regulator • Power : 230 V, 50Hz • Warranty : Minimum of 2 Years (Mandatory)[Otherwise tender will be cancelled] 	Preferred Make/Model : Systronics 128+126 /Equivalent
46		Shaker incubator	<ul style="list-style-type: none"> • Volume/Size : 285Lit/ 20''x20''x24'' • Shaking Tray : 18'' x 18'' • No. & Vol of Flask : 15 nos 250 ml • Shelves : 2 nos • Temp Range : Ambient to 90C • Controller : PID • Shaking Speed : 20-250 RPM • Material : Inner Chamber with SS304 <p>Outer body with MS -powder coated Door-Inner Glass Door & Outer Glass View Door</p> <ul style="list-style-type: none"> • Features : Auto Variac Control , RPM Counter, Digital Timer, Fluorescent Lights • Power : 220/230V , Single Phase AC , 4KW • Warranty : Minimum of 2 Years (Mandatory)[Otherwise tender will be cancelled] 	Any Good Make with ISO 9001: 2008 certification

47		Horizontal and rotary shakers	<ul style="list-style-type: none"> • ** Supply complete with suitable voltage stabilizer • Heavy duty mechanical horizontal & Rotary shaker • Angle iron construction and Mild Steel Tray with size of 36" x 18" x 4" • Epoxy paint • Fly nut, steel rod with rubber tube lining to accommodate different sizes of flask • Auto-Variac controlled Shaking Motion • Speed Range : 50-150 r.p.m • Power Requirement :220 Volts Single Phase A.C • Warranty : Minimum of 2 Years (Mandatory)[Otherwise tender will be cancelled] 	Any Good Make with ISO 9001: 2008 certification
48		Soil Tensiometer	<p>Measuring Unit : kPa (Kilo Pascal) Range : 0-100 kPa Accuracy : ± 1% Display : 2 Line 28 Character LCD which displays Date, Time, Tube Number and Moisture reading in kPa</p> <p>Memory : 1 GB Response Time : Less than 10 seconds</p> <p>Stabilization Time : 3 seconds approximately from power-up</p> <p>Battery : 9 Volt Alkaline</p> <p>Software : Windows Graphical User Interface GUI) to download.CSV data file for importing to Excel.</p> <p>Complete with:</p> <ul style="list-style-type: none"> ➤ SSTOPPER Replacement Stoppers 50/pk - 1 Pkt. ➤ SSTN Replacement Gauge Needle 100/pk - 1 Pkt. ➤ SSTAUGER Auger for Tube installation - 1 No. <p>To be supplied with tensiometer tubes, size : 30, 45, and 60 cm 5 no each</p>	TK Systems SST102G Meter with Logger
49		Soil Compaction Meter/ Penetrometer	<ul style="list-style-type: none"> • Takes penetration/compaction readings to a depth upto 45 cm • Should have depth sensor with 2.5 cm increments • Penetration resistance measured by internal load cell • Option to connect GPS device • Equipped with internal data logger and RS-232 port <p>Specifications:</p> <p>Measurement Units : Cone Index (PSI or kPa)</p> <p>Resolution : 2.5 cm, 5 PSI</p> <p>Accuracy : ± 1.25 cm Depth, ±15 PSI Pressure</p> <p>Range : 0 to 45 cm, 0 to 1,000 PSI</p> <p>Battery : Field Replaceable 4 AAA alkaline b</p> <p>Data Logger/Memory : More than 500 datas</p>	Spectrum SC900/Equiv alent
50	Genetics and Plant Breeding	Plant Growth Chamber	<ul style="list-style-type: none"> ▪ Pre-fabricated double-walled chamber with 75mm thick insulation with puff between interior. ▪ Inner chamber is made up of S.S. And outer MS duly spray painted. ▪ Double walled door and full view inner Plexiglas door. ▪ Forced air circulation for maintaining temperature uniformly. ▪ provided Photosynthesis Active Radiation Lamp (PAR) Controlled By Photoperiodic Timer ▪ Temperature range : 5°C to 45°C±1°C ▪ Humidity range : up to 90% RH ±3% RH ▪ Microprocessor controller with LED display and Sensor failure 	Any good make (Indigenous)

			<p>alarm</p> <ul style="list-style-type: none"> Power cords and ground plugs to operate on 220 V/440 V single or three phases. Power sockets on the panel (115/1/60-9 Amps for standard). Capacity: 280 L (10 cft) Warranty: Mandatory 2 years 	
51		BOD Incubator Shaker Combined High & Low Temperature	<ul style="list-style-type: none"> Incubator Shaker should have Powerful triple eccentric drive mechanism with PID microprocessor controller, large easy-to-read LCD display, non-volatile memory function, Alarms programmed to warn of set point deviations Temperature: +5°C to 60°C ±1°C Timer: 1 minute to 250 hours Shaking speed: 30-600 rpm ±1 rpm System should have Mirror-finished stainless steel interior; System should be provided with 50ml x 4, 100ml x 4, 250ml x 3, 500 ml x3; Maximum capacity should be 1000ml x 5; Platform Size should be 340 x 370mm System power consumption should be 540W System should operate at 220-230V 50/60Hz System should be CE, ISO certified. Warranty: Mandatory 2 years <p><u>Accessories for above:</u> Automatic Relay Type Voltage Stabilizer, Digital Display With Low & High Voltage Auto Cut Out Device And Copper Coiled Transformer: (Instead Aluminium Coated Transformer): Capacity :5 KVA Input Voltage : 160 To 270 Volts ± 10% Output Voltage :220/230 V, Ac</p>	Imported(JS Research Korea/Jeotech Korea /Equivalent) or Branded Indigenous (Rivotech/Equivalent) with ISO 9001: 2008 certification
52		Laminar Air Flow(All Stainless Steel body)	<ul style="list-style-type: none"> Laminar Air Flow (All Stainless Steel body) Type : Horizontal Working Space : 3'x2'x2' Motor : ¼ HP, 1440 R.P.M , 230V (blower assemblies in generic execution) Material : Exterior & Interior: 304 grade Stainless Steel Sheet Work table - 304 Quality Stainless Steel Sheet Side cover - 6mm thick glass Front Shutter: Acrylic Sheet Lights : Fluorescent & UV Tubes HEPA Filter Area : 36''x 24'' Bio-clean Workspace: 35'' x 24'' x 23'' Air cleanliness: ISO Class 5 (ISO 14644-1:1999 E) Air Velocities :0.45 ±0.05 mps Supplied With: HEPA FILTER(Separation less Mini pleat Anti-microbial HEPA Filter of EU 13 grade with an efficiency of 99.999% on mono disperse, down to 0.3 Microns), PRE-FILTER (Up to 5 Microns), UV Tube, Tube Light, Blower motor , Gas Cock , Stainless Steel Top , Glass both side and Transparent Acrylic Front Shutter Warranty: Mandatory 2 years 	Klenzaid'sKl enzFlow™ or Microflow
53		Sequential AC Timer	<ul style="list-style-type: none"> Technical Specification: Timer's powered output operates two air conditioners up to 2 ton each (will arrange one more phase for 2 ton A/C), alternately. Minimum ON/OFF cycle 30 min. Input: 110/220 VAC, Phase single. Ambient: 5° - 45°C, RH up to 85% normally. Size 10 × 30 × 15 cm. Wt. 1Kg Warranty: Mandatory 1 year 	Any Good Make
54		Light Timer Controller	<ul style="list-style-type: none"> 15 minutes adjustable time-setting slot. Total circuit mounted in a box made of CRCA sheet with powder coating 	Any Good Make

		<ul style="list-style-type: none"> ▪ The timer is provided with switches, indicating lamps, timer unit, input and output terminal points. ▪ Power load: 3KW ▪ Warranty: Mandatory 1 year 	
55	Autoclave (Imported 80 L) (1 no.)	<ul style="list-style-type: none"> ▪ Microprocessor manual set digital PID controller and Capacity: 80L ▪ Exterior: Heavy duty Epoxy resin powder coated steel; Interior: SS 304 ▪ Heater: 3-5 kW ▪ Temperature: 110°C-135°C ▪ Sterilization timer: 0-99 min ▪ Working pressure: 2.0 kg/cm² at 132°C ▪ Safety: Over temperature, over pressure, over current protector: safety release valve ▪ Basket: 2EA of SS wire baskets ▪ Power input: 220V; 50Hz ▪ Warranty: Mandatory 2 years 	LabTech
56	Hot Air Oven	<ul style="list-style-type: none"> ▪ Operating temperature range: 50 to 200°C ▪ Double walled chamber with Inner wall made of stainless steel SS grade and powder coated outer surface ▪ Inner chamber size of 45"×45"×45" with 3 stainless steel trays with holes. ▪ Three heating elements on three sides of the equipment for uniform temperature on all shelves. ▪ Variable microprocessor based digital temperature controller with digital display and thermometer should be provided separate ▪ Operational inputs: 220-230V; 50/60Hz <p>Warranty: Mandatory 2 years</p>	Any Good Make with ISO 9001: 2008 certification
57	Bench Top pH Meter	<ul style="list-style-type: none"> ▪ Highly precision pH meter for continuous reading of pH (0-14 ±0.01) ▪ Solution Temperature: 0 to 100° C ▪ Ambient Temperature: -40 to 70° C ▪ Digital LED display ▪ Detachable electrode with replacement facility ▪ Warranty: Mandatory 1 years including electrode 	Eutech or Hanna
58	Analytical Balance : 0.1mg-220gms	<ul style="list-style-type: none"> ▪ Motorized internal calibration ▪ LCD segment backlight display ▪ Capacity up to 220g and readability up to 0.01 mg ▪ Operating temperature : ±5°C - 40°C ▪ Repeatability : ±0.01 mg ▪ Linearity: ±0.01m g ▪ Setting Time: about 2s ▪ Sensitivity Accuracy: 2.0x10⁻⁶ ▪ Pan size: 100 mm ▪ Warranty: Mandatory 2 years 	Mettler or Satorius
59	Non-refrigerated Table Top Centrifuge	<ul style="list-style-type: none"> ▪ High speed up to 15,000 rpm/23,000 rcf ▪ Fully Programmable, Single-knob control with LCD-display. ▪ Efficient cooling system, pre-selection from 0°C-40°C ▪ Maintenance-free brushless drive motor ▪ Magnetic rotor identification prevents over speeding rotors ▪ Motorized (Soft close) lid lock system. ▪ Angle rotor: 24 x 1.5/2.0 ml and 6 x 5.0 ml ▪ Warranty: Mandatory 2 years 	Remi /Equivalent

60	Water Bath	<ul style="list-style-type: none"> ▪ Microprocessor Controller ▪ warning & Safety Functions ▪ External Circulation Large LED Display ▪ Temperature: 0 - 100 °C ± 0.2°C ▪ Temperature control: PID ▪ Bath capacity: 5-8 litre ▪ Heater capacity: 2000W ▪ Warranty: Mandatory 2 years 	Any Good Make with ISO 9001: 2008 certification
61	PCR Machine	<ul style="list-style-type: none"> ▪ Thermo block, 96 × 0.2 ml tubes, 60 × 0.5 ml PCR Tube, or 96-well PCR plate with three independent temperature zone ▪ Heating rate: 2-4 °C/s; Cooling rate: 2-3 °C/s ▪ Lid Temperature range: 37 - 110 °C ▪ Block Temperature Accuracy: ± 0.2°C ▪ System with RS-232/ Ethernet interface, control panel, data storage card, lid with an effective evaporation prevention control, self-functionality test, etc. ▪ Power: 220-230 V, 50-60 Hz. ▪ Compatible accessories and consumables complete with the system ▪ On-line UPS (1KVA) for at least 2 hrs backup ▪ Warranty: Mandatory 2 years 	Thermo Fisher or Bio Rad or Eppendorf
62	Dual Mini Vertical SDS PAGE Unit + Power Pack	<ul style="list-style-type: none"> ▪ 10-well, 1.0 mm thickness; 4-gel system including 5 combs, 5sets of glass plates, 2 casting stands, 4 casting frames, sample loading guide, electrode assembly, companion running module, tank, lid with power cables, mini cell buffer dam. ▪ PowerPac HV power supply: 100-240 V ▪ Warranty: Mandatory 1 year 	Bio-Rad
63	Horizontal Electrophoresis Unit with power supply	<ul style="list-style-type: none"> ▪ Standard Submarine Gel Unit (15 x 15 cm) including: Buffer Chamber Assembly, 16 well (1mm) combs-2 numbers, Safety Lid, Colored Loading Strips High Voltage Leads, Buffer Recirculation Ports-2 numbers, Running Tray w/Casting Gates ▪ Additional comb: 25 well (1mm) and 16 well (1mm) ▪ Imported and branded power supply: 10-300V; 4-500mM; 90W ▪ Warranty: Mandatory 1 years 	Hoefler
64	Hot Plate Magnetic Stirrer	<ul style="list-style-type: none"> ▪ Top Plate Dimension : 18cm x 18cm ▪ Top Plate Material : Ceramic Top ▪ RPM : 100-1000rpm ▪ Max Capacity : 5L ▪ Temp Range : 150-500°C ▪ Max Load : upto 11 Kg ▪ Power Requirement : 240VAC-50Hz-4.7A-1115W ▪ Warranty : 2 Years(Mandatory)[Otherwise tender will be cancelled] 	Tarson SPINOT 6030 /Equivalent
65	Vortex Mixer	<ul style="list-style-type: none"> ▪ Powerful motor for INSTANT vortexing ▪ Continuous or "touch" operation ▪ Q-Drive™ dynamic balancing system ▪ Variable speed from 200 to 3200 rpm ▪ Temperature: 5-50°C <p>Warranty: Mandatory 1 year</p>	Any good make
66	Slide Callipers	<ul style="list-style-type: none"> ▪ Resolution: 0.01mm or .0005"/0.01mm ▪ Repeatability: 0.01mm / .0005" ▪ Display: LCD ▪ Length standard: ABSOLUTE electromagnetic induction linear encoder Max. response speed: Unlimited ▪ Battery: Solar battery ▪ Warranty: Mandatory 1 year <p>Preferred Make/Model:</p>	Mitutoyo/Equivalent
67	Rice polisher	<ul style="list-style-type: none"> ▪ Motor: 400W 	Any good

		(mini)	<ul style="list-style-type: none"> ▪ Speed 750-1450 rpm ▪ Constructed from high grade cast iron and steel. ▪ Accessories: Spanner, Cleaning brush ▪ Warranty: Mandatory 1 year 	make
68		Rice DE husker (mini)	<ul style="list-style-type: none"> ▪ Capacity on paddy will be 50kg/hr. ▪ Size of the rubber roll: 35(W)×100mm(D) ▪ Motor: 400W ▪ Accessories: Spanner, nylon brush, Rubber roll ▪ Warranty: Mandatory 1 year 	Any good make
69		Analytical Balance : 0.1mg-220gms	<ul style="list-style-type: none"> • Maximum Capacity :220gms • Readability :0.001 gm • Repeatability (Test Weight) :0.001 gm • Adjustment :Internal • Weighing Pan Diameter :90mm • Interfaces :RS-232 • Housing :Die-cast aluminium, plastic ABS , Glass Wind Shield • Linearity :± 0.002gm • Temperature accuracy (±) :3 ppm/°C • Resolution :0.1 mg • Warranty : 2 years (Mandatory) 	Metler Toledo ME204 /Equivalent
70		Stereo Zoom microscope with camera and compatible accessories	<ul style="list-style-type: none"> • VIEWING HEAD :35 degree inclined trinocular head; binocular: trinocular=50: 50; interpupillary distance 50-76mm; fixed eyepiece tube with lock screw. Trinocular Head with Trino Port for attach Microscopic Camera. • EYEPIECES : High eye-point wide field plan eyepiece PL 10x/23mm, diopter adjustable. Focusable front lens, Provision to mount micrometric graticules. • ZOOM RANGE : Zoom range: 0.8x-10x, zoom ratio: 12.5 : 1; built-in aperture diaphragm; click stop for 0.8x, 1x, 1.5x, 2x, 3x, 4x, 5x, 6x, 8x, 10x. • MAIN OBJECTIVE: 1x Standard Objective with Working Distance 90mm. • BODY : Coarse and fine coaxial focus system, integrated body with focus holder, coarse range: 50mm, fine precision 0.002mm. • BASE : Plan base with transmitted illumination (work with external 5W LED fiber); built-in 360 degree rotatable mirror. • ILLUMINATION: 5W LED light box (size: 270 x 100 x 130mm) with single fiber (500mm), color temperature 5000-5500K; operating voltage 100-240VAC/50-60Hz, output 12V for Transmitted Spot. • 5.5 Mega Pixel DGI 530 HDMI Camera image on HDMI mode. USB ouputoptional, can connect with PC and use software. 60fps at 1080P, fast framerate, Also support HDR. Support SD Memory card, Max 32 GB. Camera Sensor : ½.86 inch Full HD CMOS. Resolution : 2592 X 1944(8 Bit) Pixel Size : 2.8 x 2.8µm. Output : HDMI, USB, SD Card. DIGICAM live preview, measurement with scale bar and live measure image capture software. • Warranty : 2 Years (Mandatory) 	Dewinter 'Zoomstar-Vi' Parallel Beam TrinocularStereozoom Microscope With 'Dgi-530 Hdmi' Hd Resolution Camera Attachment /Equivalent
71		DSLR Camera	24.3 Mega Pixel camera with D-ZOOM KIT: AF-P DX NIKKOR 18-55mm f/ 3.5-5.6G VR + AF-P DX NIKKON 70-300mm f/4.5-6.3G ED VR)# Supplied complete with Carrying case & 16 GB SD Card Warranty : 2 Years (Mandatory)	Nikon D 5600 with 18-55 mm + 70-300 mm lens or Equivalent
72		BOD Incubator	<p>BOD Incubator (Combined Low & High Temperature)</p> <ul style="list-style-type: none"> • Construction :Double-walled with adequate Polyurethane foar insulation. • Inner Chamber: 24 SWG <i>Stainless Steel (316 Grade) non magnet</i> polished with different shelf positions. Provide castor wheel (Heavy types). • Outer Walls:<i>CRC Steel Sheet</i>,18 SWG scraped and treated wi 	Imported(J S Research Korea/ Jeotech Korea /Equivalent) or Branded Indigenous(Rivotech/Eg

		<p>corrosive primer and finished with powder coating.</p> <ul style="list-style-type: none"> • Outer Door: The outer door shall be double walled duly insulated provided with magnetic strip gasket with proper sealing and device. • Inner Door: An <i>Acrylic/ Glass</i> door is provided. • Forced Air Circulation: Provided by a <i>multi-vane blower</i> aluminium having brass shaft. • Non CFC Refrigerator System: Done by a <i>hermetically sealed</i> in make refrigerator compressor with balance condensing unit. • Heating System: Provided by a pair of replaceable type sealed air made of <i>nickel-chromium resistance wire</i>. • Temperature Controller: Precisely done by a fully automatic processor based <i>PID (dual setting) Digital</i> temperature indicator cum controller in conjunction with <i>PT-100</i> sensor and heavy duty low voltage electrical delay relay system. Illumination system with timer setting facility shall be provided. • Should be fitted with Castor wheel. • Warranty : Minimum of 2 Years (Mandatory)[Otherwise tender will be cancelled] <p>Technical Specification:-</p> <p>Temperature Range : 0°C to $60^{\circ}\text{C} \pm 0.5^{\circ}\text{C}$</p> <p>Capacity : 6cft. /170Ltrs</p> <p>No. of Trays : 23 Numbers heavy punch type perforated</p> <p>S.S trays (<i>316 grade</i>), 22 SWG.</p> <p>Safety Device : A built in delay relay system is provided in the control circuit to safeguard the refrigeration compressor against abrupt starting due to power failure.</p> <p>Operable on : 220/230 Volts, Single phase, 50 Cycles, AC Mains.</p> <p>Volume capacity : 6 cft. /170Ltrs /50cm x 50 cm x 70 cm</p> <p>Accessories for above:</p> <p><u>Automatic Relay Type Voltage Stabilizer, Digital Display With Low Voltage Auto Cut Out Device And Copper Coiled Transformer: (Insulated Aluminium Coated Transformer):</u></p> <p>Capacity : 4 Kva</p> <p>Input Voltage : 160 To 270 Volts $\pm 10\%$</p> <p>Output Voltage : 220/230 V, Ac</p> <p>Warranty : 2 Years (Mandatory)</p>	<p>ivalent) with ISO 9001: 2008 certification (No Local Make will be entertained)</p>
73	Autoclave and accessories	<ul style="list-style-type: none"> • Type : Vertical • Inner boiling chamber size : 18" Dia. X 24" Depth /95 Ltrs (Approx) • Material : Boiling chamber - 16 gauge Stainless Steel Sheet 304 Quality <ul style="list-style-type: none"> • Outer body - 24 gauge Stainless Steel Sheet 304 quality • Basket- Perforated Stainless Steel 304 quality • Features : Digital Temperature Controller cum Timer, Safety Alarm, Pressure gauge, Safety Valve, Steam release Cock, water level indicator, ISI Mark Industrial heater • Power Requirement : 220/230 Volts, single phase, AC mains, 4 KW Load • Warranty : 2 Years (Mandatory)[Otherwise tender will be cancelled] 	<p>Any Good Make with ISO 9001: 2008 certification</p>
74	Deep freezer (-20C)	<p>-20°C Upright Solid Door Freezer</p> <ul style="list-style-type: none"> • Capacity : 340-400 Liters • Temp Range : -17°C to -24°C • No. Of Shelves /Baskets : 8 -10 • No Of Doors : 1 	<p>Celfrost BFS 345S / Thermo F400-SAEV-TSC or</p>

			<ul style="list-style-type: none"> • Power Load :140 Watt • Defrost Type : Automatic • Energy Consumption : 10.1 kWh/day • Microprocessor control and monitoring system • Warranty : Minimum of 2 Years (Mandatory)[Otherwise tender will be cancelled] 	Equivalent
75		Hot Air Oven	<p>** Supply complete with suitable voltage stabilizer</p> <ul style="list-style-type: none"> • Size :24" X 24" X 36" / 340 Ltrs (Approx) • Temperature Range : 50° C to 250° C • Accuracy :± 1°C. • Temperature control :Digital Temp. Indicator Cum controller with PT-100 Sensor . • Power Requirement :230 volts, 50 Hz, Single phase • Construction : <ul style="list-style-type: none"> ❖ 1 No Air Circulation Fan ❖ The unit is double walled construction, ❖ Inner chamber is made (304 Quality) 24 gauge Stainless Steel Sheet with highly polished. ❖ Outer Chamber is made of mild steel sheet with epoxy paint ❖ Thick glass wool insulation ❖ 3 nos Stainless steel perforated Trays ❖ Fitted with control panel main indicating neon lamp, load neon lamp, 3 Heat Rotary switch for low/medium/ high Temp. • Warranty :2 years (Mandatory) [Otherwise tender will be cancelled] 	Any Good Make with ISO 9001: 2008 certification
76		Slide warmer, Berlese Funnel, Slide Box, Different insect traps	Kindly Provide Specification	
77		Analytical Balance : 0.1mg-220gms	<ul style="list-style-type: none"> • Maximum Capacity :220gms • Readability :0.001 gm • Repeatability (Test Weight) :0.001 gm • Adjustment :Internal • Weighing Pan Diameter :90mm • Interfaces :RS-232 • Housing :Die-cast aluminium, plastic ABS , Glass Wind Shield • Linearity :± 0.002gm • Temperature accuracy (±) :3 ppm/°C • Resolution :0.1 mg • Warranty : 2 years (Mandatory) 	Metler Toledo ME204 /Equivalent
78	Agri Entomology	Digital Top Loading Precision Balance	<ul style="list-style-type: none"> • Maximum Capacity :2200gms • Readability :0.01 gm • Repeatability (Test Weight) :0.01 gm • Adjustment :Motorized Internal Calibration • Weighing Pan Size :198mm x 205mm Approx • Interfaces :RS-232 • Display :LCD • Linearity :± 0.02gm • Power Supply :AC Adaptor • Warranty : 2 years (Mandatory) 	ACZET CY2202C / Equivalent
79		Digital Top loading Balance	<ul style="list-style-type: none"> • Maximum Capacity :30KG • Readability :0.5 gm • Repeatability (Test Weight) :0.5 gm • Adjustment :External Calibration • Weighing Pan Size :9.0"x11.8" Approx • Interfaces :RS-232 	ACZET CZ 30H/ Equivalent

			<ul style="list-style-type: none"> • Display :LCD display with auto LED Backlite • Linearity :± 0.02gm • Unit of Measure :gm, kg, ounce, lb • Power Supply :AC Adapter 9V/ 500 mA • Warranty : 2 years (Mandatory) 	
80	Plant Pathology	Single Distillation unit	<ul style="list-style-type: none"> • Distilled Water Output : 4.0 Ltr/ Hr • Cooling water consumption :2Ltrs/Hr • Power Requirement : 230-250Volts, Single Phase 3.5 Kw Quartz Heaters • Biological Activity :Pyrogen Free • pH Range : 6.9-7.0 • Conductivity (S/cm) :3x 10⁻⁶ • Distillate Temperature : 65-75° C • Warranty : 2 Years (Mandatory) <p>Supply complete with accessories & Power supply and Water Softener as optional</p>	Borosil - 3361/4.0L /Riviera/ Equivalent
81		LCD projector with Projector Screen	<ul style="list-style-type: none"> • Technology : 3LCD or Equivalent • Brightness : 3200 ANSI LUMENS • Contrast Ratio : 20000:1 or Equivalent • Resolution : XGA (1024 x 768 dots) 4:3 display resolution • Projection Lens Zoom/Autofocus :Approx 1.2x Manual Zoom/Manual Focus • Throw Ratio : 1.47:1 to 1.77:1 • Audio : Built-in 16W speaker (mono) • Ports : HDMI & VGA • Functionality : Remote Control • Lamp Type : 225W type Ultra high pressure mercury lamp • Lamp Life : 10000 Hrs or more • Power Requirement : AC 100 V to 240 V, 3.4 A to 1.5 A, 50 Hz / 60 Hz • Warranty : 3 Years or More • Supply Complete with Remote Control , VGA Cable, HDMI Cable, Power Cable, , Manual , Wall Hanging Assembly , Carrying Case etc • Projector Screen Tripod type projector screen of size 6'(W) x 4'(H) 	Sony VPL-EX 430/435 or Equivalent of EPSON/Sharp/Hitachi
82		Autoclave and accessories	<ul style="list-style-type: none"> • Type : Vertical • Inner boiling chamber size : 18" Dia. X 24" Depth /95 Ltrs (Approx) • Material : Boiling chamber - 16 gauge Stainless Steel Sheet 304 Quality <ul style="list-style-type: none"> • Outer body - 24 gauge Stainless Steel Sheet 304 quality • Basket- Perforated Stainless Steel 304 quality <p>Features : Digital Temperature Controller cum Timer, Safety Alarm, Pressure gauge, Safety Valve , Steam release Cock, ISI Mark Industrial heater, Automatic pressure control switch, Water level indicator (gauge glass), Low water level cut out device</p> <ul style="list-style-type: none"> • Power Requirement : 220/230 Volts, single phase, AC mains,4 KW Load • Warranty : 2 Years(Mandatory)[Otherwise tender will be cancelled] 	Any Good Make with with ISO 9001: 2008 certification
83	Hot Air Oven	<ul style="list-style-type: none"> • Size :24" X 24" X 24" / 225 Ltrs (Approx) • Temperature Range :Ambient to 250° C • Accuracy :± 1°C. • Temperature control :Digital Temp. Indicator Cum controller with PT-100 Sensor . • Power Requirement :230 volts, 50 Hz, Single phase • Construction : <ul style="list-style-type: none"> ❖ 1 No Air Circulation Fan ❖ The unit is double walled 	Any Good Make with with ISO 9001: 2008 certification	

			<ul style="list-style-type: none"> ❖ Inner chamber is made (304 Quality) 24 gauge Stainless Steel Sheet with highly polished. ❖ Outer Chamber is made of mild steel sheet with epoxy paint ❖ Thick glass wool insulation ❖ 3 nos Stainless steel perforated Trays ❖ Fitted with control panel main indicating neon lamp, load neon lamp, 3 Heat Rotary switch for low/medium/ high Temp. <ul style="list-style-type: none"> • Warranty :2 years (Mandatory) [Otherwise tender will be cancelled] 	
84	BOD Incubator	<ul style="list-style-type: none"> • Capacity :90cm x 60cm x 60 cm /12 Cft/340Ltrs • Temperature Range :0°C , to 60°C ± 0.5°C • Temp. Control :Microprocessor Based PID Controller • No. of Tray :3nos.Trays • Power Requirement : 230 volts, 50 Hz, Single phase • Construction : <ul style="list-style-type: none"> ❖ Triple walled construction ❖ Inner Chamber with Stainless Steel (304) 22 gauge ❖ Outer wall with CRC Sheet 22 gauge with epoxy powder coated paint ❖ Glass wool Insulation ❖ Trays are with 3/4 Perforated Ball punching (304)Stainless Steel ❖ Double door system ; Inner door is made of Glass & outer door with insulated double walled sheet ❖ Heating System made of Nickel-Chromium Resistance Wire ❖ Control panel consisting of switches, indicating lamps, digital controller, speed controller etc ❖ Temperature Indicator Cum Controller with PT-100 Sensor ❖ Hermetically sealed compressor with relay and cooling coil ❖ Illumination system with fluorescent tubes and 24 hrs adjustable timer for day/night cycle ❖ Supply complete with suitable voltage stabilizer (IP:130-280V, OP:220V) <ul style="list-style-type: none"> • Warranty :2 years (Mandatory) [Otherwise tender will be cancelled] 	Any Good Make with ISO 9001: 2008 certification	
85	Refrigerator	<ul style="list-style-type: none"> • Capacity : 185-195 Liters • Door type : Single Door • Defrosting System: Frost Free • Cooling Technology: Stay Cool • Star Rating : 3 Star • Features :Anti-B Technology, Cool Shower Technology, Easy store and serve bins, Intelligent Operations, Low Starting Voltage, Quick Freeze, Soft Freeze Technology • Warranty : 1 year • Colour : Silver/Black/Cherry Red 	Whirlpool 200 IM Powercool Roy /Samsung RR20N182X R8/Equivalent	
86	Centrifuge (3000 rpm)	Cole- Parmer 6 place variable speed, 3000-4000rpm, 220V,WW-83058-42; Max RCF: 1830 x g		
87	Deep Freezer	Energy Consumption (kWh/yr):530; Cooling Technology Freezer Static, 460 lit; 141 cm × 84.5 cm × 74 cm, with handel and door lock, -20°C to -40°C, indicator lights	HAIER, HCF-460HTQ/Equivalent	

88	Single Beam Visible Spectrophotometer	<ul style="list-style-type: none"> Spectrophotometers should be supplied with Bi-directional RS232 interface, mains cable, instruction manual, short form operating instructions and 10mm cell holder. Lithrowmonochromator with 1200 lines/ mm holographic grating, coated optics. Wavelength range : 325-1000nm , Wavelength Accuracy :< 1nm Large Seven Segment bright LED for readouts. Photometric Range : -0.3 -3A, 0 -200%T, 0 - 9999C Photometric Accuracy : 0.005A or 1% whichever is greater Photometric Noise : less than $\pm 0.0002A$ at 500nm Wavelength Precision: 0.1nm, Bandwidth : 8nm Stray light :better than 0.05%, Stability : $\pm 0.001A/hr$ Automatic Peak Seek, Automatic Self test and Calibration 4 position cell manual changer with 4 x 10mm Cell Holder 10 mm Path length Quartz Cuvette Warranty : 2 Years 	Perkin Elmer-Lambda 325 / Cecil-CE 1011/ Equivalent
89	RO Water purifier	RO Water Purifier with storage facility, UV& Iron Guard	Aquaguard/ Equivalent
90	Laboratory Tabletop Centrifuge	<ul style="list-style-type: none"> Upto 10000 rpm Digital Speed Indicator Stepless speed regulator 0-60 minutes digital countdown timer Safety Lid interlock to prevent cover opening during centrifugation Press Switch for quick acceleration to full speed with rotor heads (8x15ml , 6x50ml etc)and accessories Warranty : 2 years(Mandatory) 	Remi/ Equivalent
91	Pressure Chamber/Leaf Water Potential System	<ul style="list-style-type: none"> System should be based on thermocouple hygrometer System should be able to measure In-situ Leaf/Plant Water Potential System should have option to instant / continuous monitoring of Leaf water potential. Measure & calculated parameters : In-Situ Stem Water Potential, Osmotic Potential, Pressure Volume Curves, Measure Stomatal Closure & Cavitation, Permanent Wilting Pressures System should supply with sensor & logger/ meters with all required accessories Logger/Meter should have memory of more than 500 data sets Warranty : 2 years(Mandatory) 	ICT PSY -1 or equivalent
92	Data Logging Universal Handy Moisture Testing Machine	<ul style="list-style-type: none"> Handy Moisture Meter Digital universal moisture meter used to find out the moisture content of food grains, pulses, oil seeds and vegetables seeds etc by principle of Resistance Grinding Facility to make sample uniform Auto. Calibration- No thickness Chart. Range - 3.5 to 40% provided with temperature sensor. 2 x16 character alphanumeric LCD display. Recorded data can be transferred to PC. Body and test cap should be of mild steel. Data logging with data storage capacity of minimum 200 readings. Warranty : 2 years (Mandatory) 	Any Good Make

93		Digital Soil Moisture Meter	<p>Standard tensiometer consists of a plastic tube with a ceramic cup at the bottom end with 15,30,45,60 and 75cm soil depth. Supplied with one Standard Gauge and auger for Tube installation</p> <p>Measuring Unit : kPa (Kilo Pascal)</p> <p>Measurement Principle : Time-domain measurement methods</p> <p>Range : 0-100 kPa</p> <p>Accuracy : $\pm 1\%$</p> <p>Display : 1 Line 12 Character LCD which displays Moisture reading in kPa</p> <p>Response Time : Less than 10 seconds</p> <p>Stabilization Time : 3 seconds approximately from power-up</p> <p>Battery : 9 Volt Alkaline/4 AAA alkaline batteries</p> <p>Data Logger : Around 4000 measurements with GPS/DGPS</p> <p>Warranty : 2 years (Mandatory)</p>	Spectrum or any good make
----	--	------------------------------------	--	----------------------------------

94	Seed Science & Technology	Refrigerated Cooling Centrifuge	<ul style="list-style-type: none"> • High speed up to 30,000rpm/65,000g or above • Rotor Head : 6x50ml, 12x1.5-2.0ml • Fully Programmable, Single-knob control with LCD-display. • Efficient cooling system, pre-selection from -10°C to +40°C • Maintenance-free brushless drive motor • Magnetic rotor identification prevents over speeding rotors • Motorized (Soft close) lid lock system. • 2 Years warranty • Heads: 24x1.5ml-2ml, 48 x 1.5 - 2.0 ml, 6x50ml, 8x50ml, 12x 1.5- 2 ml 	Sigma 3-30K or Harmle Z36HK or HerolabUnicenHR or Equivalent
95		Field Portable Pulse Modulated Chlorophyll Fluorometer	<ul style="list-style-type: none"> ➤ The instrument should be based on PAM technique, portable and lightweight ➤ System should have Blue /Red LED measuring light for longer life ➤ LED light source for saturation pulses to avoid heating to leaf surface; ➤ Saturation pulse should be up to 5000 $\mu\text{molm}^{-2}\text{s}^{-1}$ or more ➤ Far red light for excitation of Photosystem-I ➤ PIN photodiode detector ➤ Data memory for more than 20,000 saturation pulse analyses/full trace ➤ Touchscreen display (more than 6 x 6 cm) ➤ Ports: Ports for fiberoptics, USB cable, external light source, leaf clip, Barcode Scanner and auxiliaries for future attachment ➤ Parameters: Ft, Fo, Fm, F, Fo', Fm'. PAR, leaf temperature and relative humidity, Fv/Fm, Y(II), qL, qP, qN, NPQ, Y(NPQ), Y(NO) and ETR (electron transport rate) ➤ System should have option for Fitting Routines/curves: Two routines for determination of the cardinal points α, Ik and ETRmax of light curves ➤ Standard Leaf Clip should have Leaf Temperature & PAR Sensor with RH sensor ➤ Leaf clip with PAR, leaf temperature and relative humidity, permits estimation of electron transport rates driven by natural radiation. ➤ Warranty : 2 Years 	Heinz Walz Mini PAM II or equivalent
96		Water Bath Shaker	<ul style="list-style-type: none"> • Tank :High grade SS tank • Capacity : 5 to 8 litres • Temperature range : Ambient to 99° C • Temperature accuracy : $\pm 0.2^\circ \text{C}$ • Temperature control : Digital PID control • Timer : 0.1 Hour to 99.9 	Any Good Make

			<ul style="list-style-type: none"> Hours & continuous Safety protection : User settable and fixed thermal cutout Display : Digital display of temperature Alarm : Low level water alarm, safety shut down audible/visual alarm Operating voltage : 230 ±10VAC, 50 Hz. Tank design for easy cleaning and draining Steel holder for tubes (1.5/2 ml, 5ml, 15 ml) and Flasks (50, 100 & 250 ml) Powder Coating Paint Finished With Shaking Facility : RPM 50-200 Warranty : 2 years 	
97		Photocopier	<ul style="list-style-type: none"> Maximum Copy speed:-20 CPM Paper size (original/Image):- A3/A3 RAM (MB):- 256 MB Zoom:- 50 to 200% Category:- Duplex Networking: Yes Supplied complete with suitable voltage Stabilizer (IP-130-280V,OP: 220V) Warranty : 2 Years 	Canon Digital Photo Copier Machine iR-2520W /Equivalent
98		A.C.Machine	<p>Installation & Commissioning of 1.5 Tr Inverter Air Conditioner with Suitable Voltage Stabilizer</p> <p>Capacity : 1.5 Tons BEE Start Rating : 3 Star AC Type : Split Refrigerant : R 410A Compressor : Dual Rotar Inverter Filter : 7 Advance Filter Cleaning : Blow Cleaning Display : Hidden Display Condenser Coil :Copper condenser IDU,ODU and Installation kit Noise Level Indoor : ≤ 65 DB Features : 5 Sensors, Copper pipe , Anti Dust, Auto Restart, Auto Swing, Easily Removable Panel, Energy Saver, Fresh Air Ventilation, Inner Groove , Memory Function, Remote, Self Dia, Sleep Mode, Timer, Turbo Mode Remote Control : Yes Warranty : 10 Years on compressor & 4 Years comprehensive warranty Installation : Standard Installation</p> <p>Supply complete with suitable voltage stabilizer(130V-300V, upto 12amp Load Capacity, Metal Cabinet, Advanced Time Delay Function & 3 years warranty)</p>	Blue Star BS-3CNHW18R BFU with V Guard VWR 400/ Equivalent of Carrier or Daikin or Mitsubushi
99		LCD Projector with Projector Screen	<ul style="list-style-type: none"> Technology : 3LCD or Equivalent Brightness : 3200 ANSI LUMENS Contrast Ratio : 20000:1 or Equivalent Resolution : XGA (1024 x 768 dots) 4:3 display resolution Projection Lens Zoom/Autofocus :Approx 1.2x Manual Zoom/Manual Focus Throw Ratio : 1.47:1 to 1.77:1 Audio : Built-in 16W speaker (mono) Ports : HDMI & VGA Functionality : Remote Control Lamp Type : 225W type Ultra high pressure mercury lamp Lamp Life : 10000 Hrs or more Power Requirement : AC 100 V to 240 V, 3.4 A to 1.5 A, 50 Hz / 60 Hz Warranty : 3 Years or More Supply Complete with Remote Control , VGA Cable, HDMI 	Sony VPL-EX 430/435 or Equivalent of EPSON/Sharp/Hitachi

			<p>Cable, Power Cable, , Manual , Wall Hanging Assembly , Carrying Case etc</p> <ul style="list-style-type: none"> • Projector Screen Tripod type projector screen of size 6'(W) x 4'(H) 	
100		Digital audio-recording console with dedicated computer system, sound system and other accessories including editing software	Digital audio-recording console with dedicated computer system, sound system and other accessories including editing software (on turn key basis) I unit	
101		DSLR Camera with accessories	<ul style="list-style-type: none"> • Sensor: 24.2MP APS-C CMOS 4, 23.5 x 15.6mm • Image processor: EXPEED 4 • AF points: 11-point AF, 1 cross-type • ISO range: 100 to 25,600 • Max image size: 6,000 x 4,000px • Metering zones:420 pixel RGB sensor • Video: 1920 x 1080 at 60p, 50p, 30p, 25p, 24p • Viewfinder: Optical pentamirror, 95% coverage • Memory card: SD/SDHC/SDXC UHS I • LCD: 3.0-inch fixed, 921K dots • Max burst: 5fps • Connectivity: Bluetooth • Warranty : 2 years 	Nikkon D 3500 with D-ZOOM KIT: AF-P DX NIKKOR 18-55mm f/3.5-5.6G VR + AF-P DX NIKKOR 70-300mm f/4.5-6.3G ED VR / Equivalent
102	Office of The Dean	Installation of CCTV at different point of F/Ag Building	12 nos40 Mtr range IR Vandal Proof Bullet Camera , 5 nos 40 Mtr range IR Vandal Proof Dome Camera, 32 Channel DVR, 4TB Surveillance HDD, 32" LED Monitor, 12 V DC-10Amp SMPS, 2500 Mtr 3+1 100% Copper cable, Installation & Commissioning with Caching , DC Jack, Brush BNC Connector , 4x4 PVC Box, Iron Angels , 6U Rack etc	Hikvision (DS-2CE56D0T-VPIR3E)+ Hikvision (DS-2CE16D0T-VFIR3E)+D S-7116HGHI-F1/Equivalent of Vista/CPPL US
103		Water Purifier cum cooler	Eureka Forbes-120FSS - Full Stainless steel body water purifier cum cooler with 120 Lit Storage capacity along with iron guard	Eureka Forbes-120FSS/Equivalent
104		LCD Projector with Projector Screen	<ul style="list-style-type: none"> • Technology : 3LCD or Equivalent • Brightness : 3200 ANSI LUMENS • Contrast Ratio : 20000:1 or Equivalent • Resolution : XGA (1024 x 768 dots) 4:3 display resolution • Projection Lens Zoom/Autofocus :Approx 1.2x Manual Zoom/Manual Focus • Throw Ratio : 1.47:1 to 1.77:1 • Audio : Built-in 16W speaker (mono) • Ports : HDMI & VGA • Functionality : Remote Control • Lamp Type : 225W type Ultra high pressure mercury lamp • Lamp Life : 10000 Hrs or more • Power Requirement : AC 100 V to 240 V, 3.4 A to 1.5 A, 50 Hz / 60 Hz • Warranty : 3 Years or More • Supply Complete with Remote Control , VGA Cable, HDMI Cable, Power Cable, , Manual , Wall Hanging Assembly , Carrying Case etc 	Sony VPL-EX 430/435 or Equivalent of EPSON/Sharp/Hitachi

			<ul style="list-style-type: none"> Projector Screen Tripod type projector screen of size 6'(W) x 4'(H) 	
105		Photo Copier Machine	<ul style="list-style-type: none"> IR 2525 with DADF, Maximum Copy speed:- 25 CPM Paper size (original/Image):- A3/A3 RAM (MB):- 256 MB Zoom:- 25% to 400% Category:- Duplex Networking: Yes Supply complete with suitable voltage Stabilizer (IP:-130V-280V;OP:-220V) Warranty : 3Years 	CANON DIGITAL PHOTOCOPIER MACHINE MODEL NO-2525W /Equivalent
106		Video Camera along with tripod	<ul style="list-style-type: none"> Sensor Type :1 / 5.8 Type (3.1 Mm) Back-Illuminated Exmor R® Cmos Sensor Effective Pixels (Video): Approx. 2.29 Megapixels (16:9) Effective Pixels (Still Image): Approx. 2.29 Megapixels (16:9)/Approx. 1.71 Megapixels (4:3) Image Processor: Bionz X™ Image Processor Optical Zoom :30x Clear Image Zoom: 60x Digital Zoom :350x Supplied Complete With Carrying Case & 16 Gb Memory Card 	SONY(HDR PJ 675) /Equivalent
107		Lapel/ Tie-Microphone	Ahuja AWM520 VL with HBM 50	
108		Mobile Tracker	RFID Based Mobile Tracker	Any Good Make
109		Laser Pointer	Logitech R400 /R 800 Laser Pointer -2.4GHz Wireless Presenter with 50-60 feet effective range & 3 years warranty	Logitech R800/R400
110		Sound System	LECTERN- AHUJA	Ahuja
111		Lawn Mower		Any Good Make
112		Road/Corridor Sweeping Machine	<ul style="list-style-type: none"> Walk Behind Scrubber Drier- Pro Auto Scrub 45e For Floor Cleaning And Vacuuming along with Scrubbing Brush & Squeezer Scrubbing Width : 450mm Effective suction width : 780mm Theoretical area coverage : 1800 m.sq/hr Working speed, : up to 4 km/h Airflow rate : 29 L/sec Vacuum Pressure : 1550 mm of H2O Power Supply : 230/50 V/Hz Total Power : 1050W Brush Motor : 550W Vacuum motor power : 500W No. of brushes : 1nos Diameter of brush : 450mm Brush Speed : 180rpm Warranty : 2 Years 	Eureka Forbes Pro Autoscrub 45E / Equivalent
113		DSLR Camera with accessories	<ul style="list-style-type: none"> Sensor: 24.2MP APS-C CMOS 4, 23.5 x 15.6mm Image processor: EXPEED 4 AF points: 11-point AF, 1 cross-type ISO range: 100 to 25,600 Max image size: 6,000 x 4,000px Metering zones: 420 pixel RGB sensor Video: 1920 x 1080 at 60p, 50p, 30p, 25p, 24p Viewfinder: Optical pentamirror, 95% coverage Memory card: SD/SDHC/SDXC UHS I LCD: 3.0-inch fixed, 921K dots Max burst: 5fps Connectivity: Bluetooth Warranty : 2 years 	Nikon D 3500 with D-ZOOM KIT: AF-P DX NIKKOR 18-55mm f/3.5-5.6G VR + AF-P DX NIKKOR 70-300mm f/4.5-6.3G ED VR / Equivalent
114		A.C. Machine	Installation & Commissioning of 1.5 Tr Inverter Air Conditioner with Suitable Voltage Stabilizer	Blue Star BS-3CNHW18R

			<p> Capacity : 1.5 Tons BEE Start Rating :3 Star AC Type :Split Refrigerant : R 410A Compressor : Dual Rotar Inverter Filter : 7 Advance Filter Cleaning : Blow Cleaning Display : Hidden Display Condenser Coil :Copper condenser IDU,ODU and Installation kit Noise Level Indoor : ≤ 65 DB Features : 5 Sensors, Copper pipe , Anti Dust, Auto Restart, Auto Swing, Easily Removable Panel, Energy Saver, Fresh Air Ventilation, Inner Groove , Memory Function, Remote, Self Dia, Sleep Mode, Timer, Turbo Mode Remote Control : Yes Warranty : 10 Years on compressor & 4 Years comprehensive warranty Installation : Standard Installation </p> <p> Supply complete with suitable voltage stabilizer(130V-300V, upto 12amp Load Capacity, Metal Cabinet, Advanced Time Delay Function & 3 years warranty) </p>	<p> BFU with V Guard VWR 400/ Equivalent of Carrier or Daikin or Mitshubushi </p>
115	Bio-control Unit	BOD incubator (For Microbial Culture)	<p> BOD Incubator (Combined Low & High Temperature) </p> <ul style="list-style-type: none"> • Construction :<i>Double-walled</i> with adequate Polyurethane foam insulation. • Inner Chamber: 24 SWG <i>Stainless Steel (316 Grade) non magnetic</i> polished with different shelf positions. Provided with castor wheel (Heavy types). • Outer Walls:<i>CRC Steel Sheet</i>,18 SWG scraped and treated with corrosive primer and finished with powder coating. • Outer Door: The outer door shall be double walled duly insulated provided with magnetic strip gasket with proper sealing and device. • Inner Door: An <i>Acrylic/ Glass</i>door is provided. • Forced Air Circulation: Provided by a <i>multi-vane blower</i> aluminium having brass shaft. • Non CFC Refrigerator System: Done by a <i>hermetically sealed</i> in make refrigerator compressor with balance condensing unit. • Heating System: Provided by a pair of replaceable type sealed air made of <i>nickel-chromium resistance wire</i>. • Temperature Controller: Precisely done by a fully automatic processor based <i>PID (dual setting)Digital</i> temperature indicator cum controller in conjunction with <i>PT-100</i> sensor and heavy duty low voltage electrical delay\relay system. Illumination system with timer setting facility shall be provided. • Should be fitted with Castor wheel . • Warranty : Minimum of 2 Years (Mandatory)[Otherwise tender will be cancelled] <p> Technical Specification:- Temperature Range : 0°C to $60^{\circ}\text{C} \pm 0.5^{\circ}\text{C}$ Capacity : 10 cft. No. of Trays : $3/4$ Numbers heavy punch type perforated S.S trays (<i>316 grade</i>), 22 SWG. Safety Device : A built in delay relay system is provided in the control circuit to safe guard the refrigeration compressor against abrupt starting due to power failure. Operable on :<i>220/230 Volts</i>, Single phase, 50 Cycles, AC Mains. Volume capacity : 10 cft </p>	<p> Imported or Branded Indigenous with ISO 9001: 2008 certification </p>

			<p>Accessories for above:</p> <p><i>Automatic Relay Type Voltage Stabilizer, Digital Display With Low Voltage Auto Cut Out Device And Copper Coiled Transformer. (Inst</i></p> <p><i>Aluminium Coated Transformer):</i></p> <p>Capacity : 4 Kva</p> <p>Input Voltage : 160 To 270 Volts \pm 10%</p> <p>Output Voltage : 220/230 V, Ac</p>			
116	ELP on Vermicom post	Electronic Balance	• 50 Kg capacity			Any Good Make
117		Electronic Balance	• 2 Kg. Capacity			Any Good Make
118	CIC	Multi parameter for measuring pH, Conductivity, Ion, ORP and Dissolved Oxygen bench Top Meters with multi parameters	a	Short description	Professional modular dual-channel instrument for measuring ion concentrations, pH, mV/ORP, rel. mV, conductivity, salinity, TDS, resistivity and conductivity ash.	Mettler Toledo / Seven Excellence™ pH/mV] with ORP Electrode or Seven Compact Duo S213 or Seven Excellence pH Meter, or Equivalent EC Meter Model: Seven Compact Cond. meter with Calibration Buffers.
	b		electrode	ORP electrode and Soil pH, Chemical pH measure electrode.		
	c		Cond. resolution	0.001 μ S/cm to 2000 ms/cm, various different units, defined by user.		
	d		Cond. accuracy	+/- 0.5%		
	e		pH-range	-2.000 to 20.000		
	f		pH-resolution	variable: 0.001 / 0.01 / 0.1		
	g		pH-relative accuracy	\pm 0.002		
	h		mV-range	-2000 to 2000		
	i		mV-resolution	variable: 0.1 / 1		
	j		mV-relative accuracy	\pm 0.1		
	k		Temperature range °C	-30.0 to 130.0		
	l		Temperature resolution °C	0.1		
	m		Temperature accuracy °C	\pm 0.1		
	n		TDS range	0.001 mg/L ... 1000 g/L		
	o		Resistivity range	0.01 ... 100.0 MOhm*cm		
	p		Salinity range	0.00 ... 80.00 psu, ppt		
	q		Display	7 inch color TFT display		
	r		ISFET pH range	0.000 to 14.000		
	s		ISFET pH resolution	variable: 0.001 / 0.01 / 0.1		
	t	ISFET pH relative accuracy	\pm 0.05			
	u	Touch Screen	Capacitive			
	v	Warranty	2 Years			

b. List of furniture with Specification

Sl. No.	Items	Specification with Technical details
1	Desk cum Chair	Godrej make-two sitter- scholar
2	Wooden chair- armed	Made of teak wood
3	Wooden Chair (without arm)	Made of teak wood
4	Small stool	Made of teak wood
5	Cushion Chair	Supreme Ornate
6	Full secretariat table	Godrej make- 4'6"x2'3"
7	Almirah-big size	Godrej make -78"x36"x19"
8	Almirah – small size	Local make – 50"x40"x20"

9	Desk cum Chair	Godrej make-three sitter- scholar
10	Full Secretariat Table	Godrej make
11	Half secretariat table	Godrej make
12	Godrej chair	Godrej
13	Small table	3'x2' made of teak wood
14	Table for Video Conference room	Any good make
15	Chair for Video Conference room	Any good make
16	Handy Garden Trolley	Any good make
17	Heavy duty Folded Trolley	Any good make
18	Lab Trolley	Any good make
19	Wheel Barrow Trolley	Any good make
20	Manual Mobile storage System.	Any good make
21	Glass fitted Book Shelf	Godrej make 72"x36"x19"
22	File Cabinet	Godrej make
23	Round Conference Table	Any good make
24	Notice Board	Alkesign ASLIB 670x540x1590 ASGPB90120 NBFC90120

c. List of computer with peripherals

Sl. No.	Item	Specification	Make model																								
1.	Desktop Computer	<table border="1"> <tr> <td>Processor</td> <td>Intel® 8th Generation i3- 8100 Quad Core CPU with 3.6 GHz speed, 2400 MHz 65W and 6 MB Cache or better</td> </tr> <tr> <td>Chipset</td> <td>Chipset compatible with the processor / Intel H370</td> </tr> <tr> <td>Monitor</td> <td>18.5 Inch LED Screen</td> </tr> <tr> <td>Memory</td> <td>4GB DDR 4 RAM - Up to 32GB DDR4-2666 Unbuffered Memory (UDIMM)</td> </tr> <tr> <td>Hard Disk Drive</td> <td>1TB SATA HDD@ 7200 RPM</td> </tr> <tr> <td>Optical Drive</td> <td>DVD Writer (quote as optional)</td> </tr> <tr> <td>Graphics</td> <td>HD Intel Integrated Graphics</td> </tr> <tr> <td>Audio</td> <td>High Definition Integrated Audio with Internal Speaker</td> </tr> <tr> <td>Ethernet</td> <td>Integrated 10/100/1000 Ethernet Controller or 802.11ac (1x1) WiFi and Bluetooth® 4.2 Combo</td> </tr> <tr> <td>Slots</td> <td>1 x PCIe x16, 1xPCIe x1, 1xPCI , SD Card Reader</td> </tr> <tr> <td>Bays</td> <td>(2) 3.5" Internal drive bays (1) ODD bay</td> </tr> <tr> <td>Ports</td> <td> Rear I/O (2) USB 3.1 Gen 1 ports, (4) USB 2.0 Ports (1) VGA video port; (1) Display Port/DVI-D/HDMI Port (1) RJ-45 network connector (2) RS-232 serial port(1) Parallel Port 3.5mm audio in/out jacks PS/2 keyboard and mouse ports Front I/O (2) 2 nos USB 3.1 Gen 1 ports , 3.5mm </td> </tr> </table>	Processor	Intel® 8th Generation i3- 8100 Quad Core CPU with 3.6 GHz speed, 2400 MHz 65W and 6 MB Cache or better	Chipset	Chipset compatible with the processor / Intel H370	Monitor	18.5 Inch LED Screen	Memory	4GB DDR 4 RAM - Up to 32GB DDR4-2666 Unbuffered Memory (UDIMM)	Hard Disk Drive	1TB SATA HDD@ 7200 RPM	Optical Drive	DVD Writer (quote as optional)	Graphics	HD Intel Integrated Graphics	Audio	High Definition Integrated Audio with Internal Speaker	Ethernet	Integrated 10/100/1000 Ethernet Controller or 802.11ac (1x1) WiFi and Bluetooth® 4.2 Combo	Slots	1 x PCIe x16, 1xPCIe x1, 1xPCI , SD Card Reader	Bays	(2) 3.5" Internal drive bays (1) ODD bay	Ports	Rear I/O (2) USB 3.1 Gen 1 ports, (4) USB 2.0 Ports (1) VGA video port; (1) Display Port/DVI-D/HDMI Port (1) RJ-45 network connector (2) RS-232 serial port(1) Parallel Port 3.5mm audio in/out jacks PS/2 keyboard and mouse ports Front I/O (2) 2 nos USB 3.1 Gen 1 ports , 3.5mm	HP Pro G1 Micro Tower Business PC / DELL OptiPlex 5060
Processor	Intel® 8th Generation i3- 8100 Quad Core CPU with 3.6 GHz speed, 2400 MHz 65W and 6 MB Cache or better																										
Chipset	Chipset compatible with the processor / Intel H370																										
Monitor	18.5 Inch LED Screen																										
Memory	4GB DDR 4 RAM - Up to 32GB DDR4-2666 Unbuffered Memory (UDIMM)																										
Hard Disk Drive	1TB SATA HDD@ 7200 RPM																										
Optical Drive	DVD Writer (quote as optional)																										
Graphics	HD Intel Integrated Graphics																										
Audio	High Definition Integrated Audio with Internal Speaker																										
Ethernet	Integrated 10/100/1000 Ethernet Controller or 802.11ac (1x1) WiFi and Bluetooth® 4.2 Combo																										
Slots	1 x PCIe x16, 1xPCIe x1, 1xPCI , SD Card Reader																										
Bays	(2) 3.5" Internal drive bays (1) ODD bay																										
Ports	Rear I/O (2) USB 3.1 Gen 1 ports, (4) USB 2.0 Ports (1) VGA video port; (1) Display Port/DVI-D/HDMI Port (1) RJ-45 network connector (2) RS-232 serial port(1) Parallel Port 3.5mm audio in/out jacks PS/2 keyboard and mouse ports Front I/O (2) 2 nos USB 3.1 Gen 1 ports , 3.5mm																										

		headphone/microphone combo jack	
		Form Factor	MT (Micro Tower)
		Power Supply	180- 310W (100V-240V) Active PFC power supply with 90% efficiency or better
		Keyboard/Mouse	USB Keyboard and Optical Mouse
		Operating System	Preloaded Genuine Microsoft Windows 10 Pro 64
		Diagnostic Tool	BIOS Diagnostics
		Security	Antivirus for 12 months
		Warranty	3 Years
2.	Laptop	Intel® 7 th Generation i3- 7020 CPU ,4 GB DDR 4 RAM, 1TB SATA HDD@ 7200 RPM, AMD Radeon Dedicated Graphics, Original Win 10Pro , 15.6” LED HD Monitor, DVD RW ODD, 1 year Onsite Warranty with 1 Year ADP with Bag	HP250G6/ Equivalent of Dell
3.	UPS	APC BX600C-IN 600VA, 230V Back UPS / Cyber Power BU 600E-IN	APC/Cyber power
4.	Printer cum scanner	HP Black and White LaserJet M 1136 Pro	HP
5.	Laser Printer	HP Black and White LaserJet 1020 Plus	HP
6.	Digital laser colour printer	HP Colour Laser jet Pro MFP M177FW	HP
7.	Scanner	HP 2000	HP
8.	Genstat Software	Latest Version	
9.	XLSTAT Base	Latest Version	
10.	MATLAB	Latest Version	
11.	LED Monitor	18.5" Resolution: 1920x1080 with power cable, VGA cable	HP/Dell

➤ **Tender Schedule:**

•	Date of Publication	:	13.02.2019
•	Last date of quotation submission	:	27.02.2019
•	Opening date of Technical bids	:	28.02.2019
•	Tender fee	:	Nil
•	EMD	:	@2.5% of quoted value by means of demand draft from any nationalized Bank in favour of Uttar Banga Krishi Viswavidyalaya
•	Details available in the websites	:	www.ubkv.ac.in

1. **Submission of bids:**

Both Technical bid and Financial Bid are to be submitted concurrently duly signed by the Authorized Company personnel. All papers must be submitted in English language.

2. **Time Schedules for the Tender:**

The Time Schedule for obtaining the Bid Documents, submission of bids and other documents etc. as per the attached list.

3. **Eligibility for Quoting:**

- Original Equipment Manufacturers (OEM) or Dealers/Distributors/Agents duly authorized by the manufacturers who are able to supply the assured quantities as per requirement & have requisite qualification for meeting the requirements as per this tender are only eligible for quoting.

- Further, vendors who were declared black listed and/or insolvent by any Govt. Concern/any Institutions in the Country for particular item or items are not eligible to participate in the current tender for that item or items.
- The University reserves the right not to accept the rate even from the lowest bidder/supplier.
- The University reserves the right to accept or reject any or all tenders without giving any reason whatsoever.

4. Annual Turnover Requirements:

Vender having average annual Turn Over for last three financial years is more than Rs.30 Lakh in India for the year 2015-16, 2016-17 & 2017-18 are eligible to participate in the Tender.

5. Submission of Tenders

5.1 General process of submission

All the documents including addendum/ Corrigendum related to the tender uploaded by the Tender Inviting Authority form an integral part of the contract. Tenderers are required to upload all the tender documents along with the other documents, as asked in the tender, through the above website within the stipulated date and time as given in the Tender. Tenders are to be submitted in two envelopes at a time, one is Technical Bid and the other is Financial Bid. The tenderer shall carefully go through the documents and prepare the required documents.

6.1 **Technical details:** (Bidders must submit Technical specification along with Catalogue of the item quoted in “**Technical Details**” Envelope.

6.2 Audited Annual Accounts for last three years **2015-16, 2016-17 & 2017-18** or during the period since formation of the Firm, if it was set up in less than such 3- year period. Bidders whose accounts are not audited must submit 26AS for the above years as available in the official website of the Income Tax Department, Government of India with other documents stated below:

Sl. No.	Category	Sub-Category	Sub-Category Description
1	Certificates	Certificates	PAN Card of the Bidder
			GST Registration Certificate
			P -Tax Registration Certificate with a copy of last return
2	Company Details	Company Details 1	Trade License/Enlistment Certificate
			Registration with Registrar of Companies
			Memorandum of Articles for Limited Companies.
3	Credential	Credential 1	Copy of the purchase order for supplying Similar nature of items at least for last 2 years in an Institute of Higher Education Brief User List preferably for users in West Bengal in an Institute of Higher Education
4	Financial Information	Payment Certificate 1	Income Tax Returns submitted for the Assessment year 2015-16
			Income Tax Returns submitted for the Assessment year 2016-17

			Income Tax Returns submitted for the Assessment year 2017-18
			GST Return for last 3 months in 2018-19
5	Product Catalogue (Coloured)		
6	Compliance Statement		

6.3 Financial Bid

Financial Bid should contain the unit price of items on FOR destination and CIF including applicable taxes. Rate of GST also be quoted. (All the required/ essential / optional accessories or incidental services should be mentioned in the hard copy of Financial Bid)**

7. TERMS & CONDITIONS:

7.1 Bid Information:

- a) The rate quoted by the bidder shall be fixed for the duration of the contract and shall not be subject to adjustment on any account.
- b) **Partial Quotation/Incomplete Quotation both for Technical and Commercial aspects may subject to cancellation of tender. However, University Authority will define the Partial Quotation/Incomplete Quotation based on the tender evaluation status.**

7.2 Evaluation of Quotation: Firstly, Technical Bid will be evaluated and thereafter Price Bids of technically qualified bidders will be evaluated for selection of vendor.

7.3 Award of Contract: The purchaser will award the contract to the bidder whose quotation has been determined to be substantially responsive both technically and commercially.

7.4 The vendor should quote and be capable to supply all the necessary items as per Tender. However, the University has the right to procure a part or a whole of the tendered items.

7.5 University enjoys the discretion to select vendor either in full or in part (item wise) for the betterment for pursuing of tender objectives.

7.6 Warranty: The manufacturer should give guarantee/warranty for a period as specified in the Item details. If the equipment installed at one location is subsequently shifted to another location, the warranty services shall continue to be provided at new location without any additional financial implications. During warranty period, if any defect in the supplied equipment is noticed by the Purchaser, the supplier or his representative shall rectify the defect or replace the defective item free of cost at the Purchaser's site at the earliest possible, latest within a period of 30 days of notification.

7.7 Adequate support service facility: The bidder/manufacturer should have adequate service support Centre in Kolkata/ Siliguri for any emergency breakdown/fault offering facility within 48 hours and should be agreeable to provide AMC facility after the warranty period.

7.8 Bidder must provide Technical Compliance Sheet duly certified by OEM as per the Tender Specification. Any non-compliance will lead to rejection of tender.

7.9 Credentials: Documents of supplying similar items in last two previous years in an Institute of Higher Education must be submitted along with the tender.

7.10 DSIR Certification: University possesses the privilege for availing the facility of procuring items at Concessional Customs Duty and without incurring any excise duty as per DSIR certification.

7.11 GST Exemption Certification: University possesses the privilege for availing the facility of procuring items at Concessional GST (5%) as per the decisions taken by GST Council.

7.12 Statutory deduction for GST and other Government taxes in the hand of the payee will be made as per the law in force.

7.13 Make & Model: Bidder must mention Make and Model in the Information Sheet as given vide Annexure-I and must send the product details/catalogue/brochure in the “**Technical Details**” folder along with Technical Compliance Sheet for each item component.

7.14 Time Schedule: The supply work must be completed within 30-45 days from the date of receipt of the supply order.

7.15 Validity of offer: A bidder should spell out in the tender that it shall remain valid for a minimum period of 180 days from the date of opening of the tender and during this period, the bidder shall not be entitled to revoke or cancel its offer.

7.16 After Sales and Service:

- i. The name and complete address of the company in India authorized by the manufacturer, to provide after sales service for the equipment should be mentioned. The appointed authorized service provider should be holding a valid certificate from the manufacturer to this effect.
- ii. The manufacturer should give an undertaking that after the warranty period, they shall provide spares and after sale service of the equipment in India for the normal life time of the equipment.

7.17 University reserves the discretion to issue work/ supply order either in full or phase wise depending upon the requirement and selected vendor will not charge any extra amount for such supply and delivery.

7.18 Place of delivery: Dean Faculty of Agriculture, UBKV, Pundibari, Cooch Behar, 736165 and should be quoted on FOR Destination Basis (i.e. Charge of Delivery from International Airport to Destination will be added in the basic quoted price or on CIF /CIP Price)

7.19 Payment Schedule: 100% Payment be made after delivery and successful installation of the item.

7.20 Performance Security:

Successful bidder should deposit Performance Security money equivalent to the 10% of the order value in the form of DD from any nationalized bank in favour of UBKV payable at Cooch Behar or suitable negotiable instruments as to be decided by the University immediately after issuing purchase order from the University. Such security will be refunded after completion of the warranty period in normal case without any accrued interest. University may forfeit the Security Money (EMD) and performance security money in the event of the following circumstances:

- i. Selected bidder withdraws the bid before expiry of its validity and after receipt of the Purchase Order.
- ii. Selected bidder does not accept the order after issuing the same or fails to enter into a contract within validity period of offer.
- iii. Selected bidder fails to supply the items within the scheduled time as specified in the Purchase Order.
- iv. If before expiry of the warranty period, the supplied items break down or do not function satisfactorily due to the cause related with the item itself or for its installation and not for any reason caused by the University Authority and the supplier denies to take the responsibility to make the supplied items in order.
- v. In case of any false submission /statement by the bidder

- vi. In case of any refusal to abide by terms and conditions or refusal to enter into a written agreement as per prefixed terms and conditions.

7.21 Quantity Changeability: Quantity as stated in the tender document may subject to change at the time of issuing purchase order due to the fund crunch or for other valid reasons.

7.22 Disposal of Disputes: In case of any dispute, the University's decision will be treated as the final and conclusive. All legal actions are subject to Cooch Behar jurisdiction only.

7.23 Conditional bid may be liable for rejection.

7.24 Discretion of the University:

- i. University may take decision about non-purchase of the said item even after selection of vendor due to its fund constraints.
- ii. University reserves the right to relax any clause as stated hereinabove for selection of responsive vender.
- iii. The Tender Selection Committee reserves the right to cancel the N.I.T. due to any unavoidable Circumstances and no claim in this respect will be entertained.

Sd/-

Registrar (Actg.)